


LUPALO POLLER

982705.0131.1 | Bollards



Bollards
4051859566960
LED
D 187, H 326



Bollard luminaire head for public sector applications. Luminaire head made of corrosion resistant die-cast aluminium, seawater resistant powder-coated, stainless steel screws. Diffuser: glass, transparent. Multi-chip LED with high-performance refractor optics. Asymmetrical light distribution Fastening of the luminaire head to a tube via a bayonet. Elegant-looking power supply via delicate steel cables between converter and LED. In order to fit the luminaire head, please order the required luminaire tube separately. Please order fuse box separately.

Colour

Colour anthracite metallic

Dimensions

Diameter D 187 mm
Height H 326 mm
Weight 3,71 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 70
Colour tolerance 5
Rated life 100000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 2

Lighting technology

Luminous flux component in the upper half-space 0
CIE Flux Code / CEN Flux Code 16 46 87 100 100
Colour temperature 4.000 K
Rated luminous flux 3.700 lm
Beam angle Down 79° / 65° / 79° / 50°
Beam angle combined Up 0°
Glare evaluation UGR (4H 8H) 37,7

Electrical

Control gear DALI
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 18
Luminaires on B16A fuse 28
System power 36 W
Luminaire efficacy 103
Inrush current / Inrush current duration 26 A / 180 μ s
Total harmonic distortion 10 %

Approbations

Type of protection IP 65
Protection class II
Conformity mark CE