


# LUPALO POLLER

982705.014 | Bollards



Bollards  
4051859566991  
LED  
D 187, H 326



Bollard luminaire head for public sector applications. Luminaire head made of corrosion resistant die-cast aluminium, seawater resistant powder-coated, stainless steel screws. Diffuser: glass, transparent. Multi-chip LED with high-performance refractor optics. Asymmetrical light distribution Fastening of the luminaire head to a tube via a bayonet. Elegant-looking power supply via delicate steel cables between converter and LED. In order to fit the luminaire head, please order the required luminaire tube separately. Please order fuse box separately.

## Colour

Colour silver metallic

## Dimensions

Diameter D 187 mm  
Height H 326 mm  
Weight 3,71 kg

## Lamp

Lamp LED  
Colour temperature 3000K  
Colour rendering index (CRI) 70  
Colour tolerance 5  
Rated life 100000 h (L80/B10)  
Photobiological safety according to EN 62471 Risk group 2

## Lighting technology

Luminous flux component in the upper half-space 0  
CIE Flux Code / CEN Flux Code 16 46 87 100 100  
Colour temperature 3.000 K  
Rated luminous flux 3.500 lm  
Beam angle Down 79° / 65° / 79° / 50°  
Beam angle combined Up 0°  
Glare evaluation UGR (4H 8H) 37,5

## Electrical

Control gear DALI  
Voltage 220 - 240 V / 50 - 60 Hz  
Luminaires on B10A fuse 18  
Luminaires on B16A fuse 28  
System power 36 W  
Luminaire efficacy 97  
Inrush current / Inrush current duration 26 A / 180  $\mu$ s  
Total harmonic distortion 10 %

## Approbations

Type of protection IP 65  
Protection class II  
Conformity mark CE