


LUPALO LATERNE

982706.004.1 | Bollards



Bollards
4051859567059
LED
D 187, H 326



Bollard luminaire head for public sector applications. Luminaire head made of corrosion resistant die-cast aluminium, seawater resistant powder-coated, stainless steel screws. Luminaire head made of die cast aluminium, powder-coated, with opal cylinder (glass). Fastening of the luminaire head to a tube via a bayonet. In order to fit the luminaire head, please order the required luminaire tube separately. Please order fuse box separately.

Electrical

Control gear	AC Strom, dim.Ph.an-/abschnitt
Voltage	220 - 240 V / 50 - 60 Hz
System power	20 W
Luminaire efficacy	43

Approbations

Type of protection	IP 65
Protection class	I
Conformity mark	CE

Colour

Colour	silver metallic
--------	-----------------

Dimensions

Diameter D	187 mm
Height H	326 mm
Weight	3,71 kg

Lamp

Lamp	LED
Colour temperature	4000K
Colour rendering index (CRI)	80
Colour tolerance	3
Rated life	50000 h (L80/B10)
Photobiological safety according to EN 62471	Risk group 1

Lighting technology

Luminous flux component in the upper half-space	55,2
CIE Flux Code / CEN Flux Code	8 30 62 45 100
Colour temperature	4.000 K
Rated luminous flux	850 lm
Beam angle Down	180°
Beam angle combined Up	180°
Glare evaluation UGR (4H 8H)	18,9