


LUPALO TOWER

982707.0031 | Bollards

Bollards
4051859567066
LED
D 187, H 326



Bollard luminaire head for public sector applications. Luminaire head made of corrosion resistant die-cast aluminium, seawater resistant powder-coated, stainless steel screws. Luminaire head made of corrosion-resistant pressure die-cast aluminium, powder-coated, with transparent cylinder (glass) and translucent anti-glare louvers. Fastening of the luminaire head to a tube via a bayonet. In order to fit the luminaire head, please order the required luminaire tube separately. Please order fuse box separately.

Electrical

Control gear	AC Strom, dim.Ph.an-/abschnitt
Voltage	220 - 240 V / 50 - 60 Hz
System power	20 W
Luminaire efficacy	41

Approbations

Type of protection	IP 65
Protection class	I
Conformity mark	CE

Colour

Colour anthracite metallic

Dimensions

Diameter D 187 mm
Height H 326 mm
Weight 3,71 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Colour tolerance 3
Rated life 50000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Luminous flux component in the upper half-space 42,3
CIE Flux Code / CEN Flux Code 6 30 71 58 100
Colour temperature 3.000 K
Rated luminous flux 810 lm
Beam angle Down 180°
Beam angle combined Up 180°
Glare evaluation UGR (4H 8H) 20,9