

Note: This template provides the minimum information elements for an SDS required by Schedule 1 of the Hazardous Products Regulations (HPR) (WHMIS 2015)

# Safety Data Sheet

## Microscopic Sulphur

### SECTION 1. IDENTIFICATION

**Product Identifier:** Microscopic Sulfur  
**Family Name:** Element - Sulfur  
**Trade Name & Synonyms:** Wettable Sulphur  
**Chemical Name:** Sulfur (Sulphur)  
**CAS Number:** 7704-34-9  
**Registration Number:** PCP# 873  
**Recommended Use:** Spraying and dusting crops for the control of fungus, mold, mites and etc..  
**Restrictions on Use:** Keep away from heat, sparks or open flames.  
**Initial Supplier:** N.M. Bartlett Inc.  
4509 Bartlett Rd  
Beamsville, ON Canada  
L0R 1B1  
(905)563-8261  
**Emergency Telephone Number:** CANUTEC (613) 996-6666

### SECTION 2. HAZARD IDENTIFICATION

Classification  
Label Elements



### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration	Common name / Synonyms	Other identifiers
Sulphur	7704-34-9	92.0%	Wettable Sulfur	

### SECTION 4. FIRST AID MEASURES

#### Inhalation:

Prolonged inhalation may cause irritation of the respiratory tract. Breathing of dust may aggravate asthma and other pulmonary disease. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur dust. Maintain adequate ventilation in area where dust is present. Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed exposure limits. Move patient to fresh air. Watch for signs of allergic reaction. Use a bronchodilator inhaler if directed by asthma patient. Keep victim warm and quiet. If not breathing, clear airway and start mouth to mouth resuscitation. If heart has stopped beating, start cardiopulmonary resuscitation (CPR). **GET MEDICAL ATTENTION.**

**Skin Contact:**

No adverse effects. Skin irritation may be aggravated in persons with existing skin lesions. Wash exposed clothing separately before reuse.

**Eye Contact:**

Sulfur dust is an eye irritant. Avoid contact with eyes, especially contact wearers. Wear safety glasses. In case of contact, immediately flush eyes with plenty of water for a minimum of 15 minutes. Hold upper and lower lids apart to insure rinsing of the entire eye surface and lids. Do not use boric acid to rinse with; sulfur is an acid irritant. **FOR SEVERE IRRITATION, GET MEDICAL ATTENTION**, preferably and ophthalmologist.

**Ingestion:**

Ingested sulfur is converted to sulfides in the gastrointestinal tract and ingestion of 10 to 20 grams has caused irritation of the GI tract and renal injury. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur. Swallowing large amounts may cause nausea and vomiting. Do not eat sulfur. For large amounts ingested, if the victim is conscious and alert, give two or more glasses of water to drink. If available, give one tablespoon of Syrup of Ipecac to induce vomiting. If vomiting does occur, give fluids again. If vomiting has not occurred in twenty minutes, the same dose of Syrup of Ipecac may be repeated one additional time. Alternatively, vomiting may be induced by touching the back of the throat with a finger. Do not give anything by mouth to an unconscious or convulsing person. **GET MEDICAL ATTENTION.**

**SECTION 5. FIRE - FIGHTING MEASURES**

**0 =Least 1=Slight 2=Moderate 3=High 4=Extreme**

**Hazard Rating:**

**Acute Health = 1**

**Fire = 1**

**Reactivity = 0**

**Contact = 1**

**Extinguishing Media:** Water fog, spray or regular foam. Do not use a direct water stream.

**Suitable Extinguishing Media:** Water fog, or regular foam. Do not use stream of water.

**Unsuitable Extinguishing Media:** Do not use solid streams of water, which could create sulfur dust clouds and cause an explosion or move burning sulphur to adjacent areas.

**Fire and Explosion Hazards:** Fire will rekindle until mass is cooled below 310°C(154°C). Cool surrounding areas with water fog to prevent re-igniting. Cool containers, tank cars, or trailer loads with flooding quantities of water until well after fire is out.

**Expose Hazards:** Prevent human exposure to smoke, fumes, or products of combustion (sulfur oxide gases). If large fire evacuate people downwind from fire. Isolate and evacuate for 2 miles in all directions. Evacuate nonessential personnel from the fire area.

**SECTION 6. ACCIDENTAL RELEASE MEASURES****Protective Equipment:**

Maintain adequate ventilation and wear a respirator or a dust mask to prevent inhalation. Wear suitable, protective clothing and safety glasses to prevent skin and eye irritation from dust.

**Personal Precautions:**

Clean up all minor spills or leaks. Repair and maintain any contaminated equipment.

**Emergency Procedures:**

Isolate spills or leak areas immediately.

**Environmental Precautions:**

Do not allow runoff to enter lakes or waterways.

**SECTION 7. HANDLING AND STORAGE****Conditions for Safe Storage:**

Containers should be stored in a cool, dry, well-ventilated area. Keep container tightly closed. Store away from flammable materials, source of heat, flame and sparks. Separate from chlorates, nitrates and other oxidizing agents. Exercise due caution to prevent damage to or leakage from container.

**Explosion Hazard:**

Avoid any conditions that might tend to create a dust explosion. Be careful not to create dust. Maintain good housekeeping practices to minimize dust build-up and dispersion. Eliminate sources of ignition. Keep away from heat, sparks and flames. Use nonferrous tools to reduce sparking. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Maintain adequate ventilation in all areas.

**Small or Large Spills:**

No flares or flames in area. No smoking. Danger of dust explosion near sparks. Sweep or shovel up spilled material using a natural fiber broom and/or aluminum shovel to prevent sparking. Place sweepings in an appropriate chemical waste container for reclaiming or disposal in an approved facility. Wash spill site after clean up is complete. Wear protective clothing during clean up: safety glasses, rubber gloves, impervious clothing, dust mask or respirator.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Individual Protection:****Appropriate****Engineering Controls:**

Maintain adequate ventilation in all areas. No flares or flames and be careful not to create dust. Eliminate sources of ignition.

**Measures****Eye/Face Protection:**

Wear suitable, protective eye safety glasses to prevent irritation from dust.

**Skin Protection:**

Wear protective clothing to help prevent skin irritation from dust. Wash skin thoroughly after handling and before eating or smoking. Wash contaminated clothing apart before reuse.

**Respiratory Protection:**

Wear dust masks and use NIOSH/MSHA approved dust respirator if airborne concentrations exceed expose limits.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Yellow colored lumps, crystals, powder, or formed shapes

**Odour:** Odorless, or faint odor of rotten eggs

**Odour Threshold:** Not available

**pH:** Not available

**Melting Point and Freezing Point:** 230-246°F (110-119°C)

**Initial Boiling Point and Boiling Range:** 832 °F (444°C)

**Flash Point:** 405°F (207.2°C)

**Evaporation Rate:** Not available

**Flammability (solid, gas):** Not available

**Upper and Lower Flammability or Explosive Limit:** LEL:35 g/m<sup>3</sup> UEL: 1400 g/m<sup>3</sup>

**Vapour Pressure:** 0mmHG at 280°F

**Vapour Density:** Not available

**Relative Density (water = 1):** Not available

**Solubility in Water:** Insoluble

**Auto-ignition Temperature:** 478-511°F (248-266°C)

**Purity:** 92.0% Min.

**Bulk Density: Lumps 75:** 115 lbs./ft **Powder:** 33-80 lbs./ft

**Extinguishing Media:** Water fog, spray, or regular foam. Do not use a direct water stream.

**Burning Sulphur:** Decomposes into TOXIC sulfur oxide gasses such as: Sulfur dioxide & Hydrogen sulfide.

**SECTION 10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Conditions to Avoid:** Keep from heat sources, sparks and open flames.

**Incompatible Materials:** Oxidizing agents may react violently. Corrosive to copper and copper alloys. Damp sulfur will corrode steel.

**Hazardous Decomposition Products:** Oxides of sulfur gasses produced by burning sulfur.

**SECTION 11. TOXICOLOGICAL INFORMATION****Likely Routes of Exposure**

Inhalation  Skin contact  Eye contact  Ingestion

**Acute Toxicity**

LC50

LD50 (oral)

LD50 (dermal)

**Oral LD (Rats)->**5050 mg/kg body weight

**Dermal LD (Rats)->**2020 mg/kg body weight

**Inhalation @ 90% LC (Rats)->**5.49 mg/L air concentration

**Skin Corrosion / Irritation:** Slightly irritating

**Serious Eye Damage / Irritation:** Minimal irritation in non-washed eyes

**Carcinogenicity, Teratogenicity, Mutagenicity:** This product does not contain any ingredient designed by NTP,

IARC, or OSHA as a problem human carcinogen.

**Exposed Limits:** No exposure limits have been established.

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** Not available

**Persistence and Degradability:** Not available

**Bioaccumulative Potential:** Not available

**Mobility in Soil:** Not available

**Other Adverse Effects:** Not available

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Product Waste:**

Dispose of content and/or container in accordance with local, regional, national and international regulations.

### **Packaging Waste:**

Dispose of content and/or container in accordance with local, regional, national and international regulations.

## SECTION 14. TRANSPORT INFORMATION

**WHMIS:** This product is not a WHMIS controlled substance

**Class B:** Flammable and Combustible material

**Division 4:** Flammable Solid

**Bulk Packaging:** Powdered Sulphur Only

**Shipping Name:** Sulphur

**Hazard Class:** 4.1 (Flammable Solid)

**ID Number:** UN1350

**Packing Group:** III

**Label:** Class 4 Flammable Solid

**Placard:** Class 4 (Flammable Solid)

**Shipping Description:** UN1350, Sulphur, 4.1, III

**Hazard Substance/Rq:** Not applicable

### **Export**

**IMDG:** Powdered all Sulphur – all packages

**Shipping Name:** Sulphur

**Hazard Class:** 4.1 (Flammable Solid)

**ID Number:** UN1350

**Packing Group:** III

**Label:** Class 4 Flammable Solid

**Placard:** Class 4 (Flammable Solid)

**Shipping Description:** UN1350, Sulphur, 4.1, III

**Hazard Substance/Rq:** Not applicable

## SECTION 15. REGULATORY INFORMATION

**Environmental:**

No Canadian Federal standards. This product, or all components, is listed on the Domestic substances list, as required under the Canadian Environmental Protection Act.

**Biodegradability:** Not applicable

**Formed Sulphur such as Flakes or Pastille, and powdered Sulphur packaged in containers Smaller than 400 kg- This product is not a WHMIS controlled substance.**

**TDG:** These products are not regulated.

**SECTION 16. OTHER INFORMATION**

For additional information, contact your technical Sales Representative. For additional Health & Safety information, call N.M. Bartlett Inc. at 905-563-8261.

The information contained herein is based on the data available to us and is believed to be correct. However, N.M. Bartlett makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof.

N.M. Bartlett assumes no responsibility for injury from the use of the product described herein.

Date of Latest Revision: February 23, 2017

---