

CAMERA SYSTEMS

InterTest, Inc.
303 State Route 94
Columbia, NJ 07832
+1 908 496 8008
https://intertest.com



Micro PTZ

29mm dia. x 83mm long 720p HD camera LED illumination Stainless steel housing Splashproof 270° pan & 95° tilt range *Digital zoom 4x Toolless focus



PTZ-35

35mm dia. x 165mm long 1080p HD camera LED illumination Stainless steel housing Waterproof 360° pan & 180° tilt range *Digital zoom 4x Easy clean decon. surfaces



PTZ-45

45mm dia. x 130mm long 1080p HD camera LED illumination Nickel plated Aluminum housing Waterproof 360° pan & 270° tilt *Digital zoom 4x



PTZ-XDMCU DVR Controller

- Built-in viewing device
- Joystick for pan, tilt, and light control
- Locking power and camera connectors
- HDMI and CVBS output
- Video recording
- Image capture
- On-board storage (micro-SD)
- Works with all PTZ-XD series camera heads
- More...



© 2023 Peerless Creations LLC.

This document provides technical information for the user. Peerless Creations LLC. reserves the right to modify the information in this document as necessary without notification. Peerless Creations LLC. holds no responsibility for any errors that may appear in this document.





			XXXXXXX
Controller Model:	PTZ-XDMCU		
Compression Format	H.264/H.265		FOR
Illumination Control	Yes	PFRLESS* CREATIONS LLC	TIET (
Video Format	MP4 (H265+AAC)		◆PAN◆
Frame Rate	60fps		PREV 🌦 ZOOM OUT
Data Storage	Micro SD 128GB Max		NEXT 🏐 ZOOM IN
Photo Format	JPG/JPEG		ESC 🤝
Image Resolution	Up to 8MP		SELECT @ CAPTURE
Image Capture	Yes	PTZ-	b
HDMI Video Resolution	1920 X 1080	3313 3310	
CVBS Video Resolution	720 X 576		
Operating Temperature	-30°C~70°C		
Power Supply	DC IN 12V < 1.5 A		
System Language	Chinese/English/German/Spanish/Polish/French	-	

Camera Model:	Micro PTZ	PTZ-35	PTZ-45
Image Sensor	1/4.4 Color CMOS	1/2.8 Color HD CMOS	
Effective Image Area	3.6mm X 2.03mm	12mm X 9.3mm	
Effective Pixel Array	1284H X 724V	1945H X 1097V	
Pixel Size 2.8µm X 2.8µm		2.8µm)	Κ 2.8μm
Signal/Noise Ratio	>43.1dB	>30dB	
Back Light Compensation		Auto	
White Balance	Auto		
Min Illumination	.001Lux	.0001Lux/1.2F	
Wide Dynamic Range	Auto WDR		
LED Illumination Yes			
Operating Temperature	-40°C~85°C	-30°C~85°C	
Cable Length	Up to 30 meters [100']	Up to 60 meters [200']	
Resolution	720p	108	30p







© 2023 Peerless Creations LLC.

This document provides technical information for the user. Peerless Creations LLC. reserves the right to modify the information in this document as necessary without notification. Peerless Creations LLC. holds no responsibility for any errors that may appear in this document.

