



Ø 45 mm Visioprobe compact camera *Industrial endoscopy*

- Pan & tilt camera
- Manual focus from 5 mm to infinity
- Wide depth of view
- 24 powerful LED
- Can be fixed on a telescopic pole
- Aluminium or stainless steel

Compatible with: Control Unit



InterTest, Inc.

303 Route 94
Columbia, NJ 07832
USA
+1 908 496-8008



CAMERA Ø45mm - ALUMINIUM

Reference: VP45A
Diameter: 45 mm
Length: 141 mm
Overall length: 152 mm
Weight: 0,45 Kg
Material: Aluminum alloy
colorless anodized
Sensor: CMOS 1/4"
0,025 Lux - 480LTV
Auto/manual
Focal: shutter 2,45 mm
Pan angle: 360°
Tilt angle: - 110° → + 110°
Field of vision: 80°
Sharpness range: from 5 mm to ∞
Remotely adjustable
Lighting: 24 LED
High brightness
Protective Saphir
window: 2 bars
Waterproofing: from -30° to +65°C
Temperature of use:

CAMERA Ø45mm - STAINLESS STEEL

Reference: VP45X
Diameter: 45 mm
Length: 141 mm
Overall length: 152 mm
Weight: 0,94 Kg
Material: Stainless steel 304L
Sensor: CMOS 1/4"
0,025 Lux - 480LTV
Auto/manual
Focal: shutter 2,45 mm
Pan angle: 360°
Tilt angle: - 110° → + 110°
Field of vision: 80°
Sharpness range: from 5 mm to ∞
Remotely adjustable
Lighting: 24 LED
High brightness
Protective Saphir
window: 2 bars
Waterproofing: from -30° to +65°C
Temperature of use:

