## **Z3Cam+4** EXPAND YOUR REACH H.265 4K IP Camera

### Model: Z9500



- Ideal for Low-Light Conditions
- Real-Time 4K Video Streaming
- 30x Optical Zoom
- Stream 4K and HD resolutions
- Power over Ethernet (PoE)
- Supports Sony VISCA™ camera control over IP and ONVIF® Profile S & T

#### NEVER BEFORE HAS STREAMING 4K BEEN SO SIMPLE AND COST-EFFECTIVE

The Z3Cam-4M<sup>m</sup> H.265 IP camera provides 4K Ultra-HD video streaming over Gigabit Ethernet networks. The Z3Cam-4M combines video compression expertise from Z3 Technology with Sony's proven 4K camera technology to provide the highest quality image at the lowest bandwidth, latency and power. This robust system brings clarity and detail to high movement and very low light conditions featuring 30x zoom with integrated auto focus. Video with this clarity is a perfect fit for virtual reality imaging, high detail data analytics, broadcast, medical, surveillance and more! Upgrade to 4K and expand your reach with the Z3Cam-4M.

#### **APPLICATIONS**

Broadcast Industrial Medical Security and Surveillance Corporate

# CE F©



Details		
Camera Features	<ul> <li>30x optical zoom in 2160p30 mode using Sony's Super Resolution Zoom</li> <li>Noise reduction algorithm for high frequency and high detail areas</li> <li>Visibility enhancer ICR (Day and Night)</li> <li>High sensitivity image processor</li> <li>Super Image Stabilizer</li> <li>Easily mount to tripod or mounting bracket</li> <li>Leverages Sony's FCB-EW9500H 4K camera module</li> </ul>	
Streaming Features	<ul> <li>H.265, H.264 or MJPEG encoded video over IP with no additional equipment and no distance limitations</li> <li>Supports 4K UHD and HD resolutions up to 30 fps (2160p, 1080p, 720p, and lower)</li> <li>Outputs RTP, RTSP, MPEG-2 TS or RTMP</li> <li>Simultaneously stream and/or record in multiple resolutions and bitrates</li> <li>Supports unicast and multicast streaming</li> <li>Compatible with Wowza Streaming Engine<sup>™</sup> and YouTube Live*</li> </ul>	
Control	<ul> <li>Z3 web interface for Control and configuration</li> <li>Pass Sony VISCA™ Camera Control Commands over IP</li> <li>Supports ONVIF® Profile S &amp; T</li> <li>Pelco-D PTZ control</li> </ul>	
Recording	Compressed USB recording	
Decoder Options	Compatible with ZEUS® HE265-DEC decoder (also available from Z3 Technology)     *in H.264 mode onl     PC decoding	
sales	@73technology.com +1.402.323.0702 www.73technology.com	

|--|

#### Specifications

Interfaces	Gigabit Ethernet, USB 3.1, Audio Input and Composite Output	
Power	PoE or 12V DC	
Power Consumption	TBD typical while encoding H.265/HEVC video	
Temperature & Humidity	Operating: -5 to 50 $^\circ\text{C}$ at 20-80% Relative Humidity	Storage: -10 to 60 °C at 20-80% Relative Humidity
Mount	1/4 20 UNC tripod screw hole on bottom of unit	
Dimensions (L x W x H)	165 x 65 x 70 mm (6.5 x 2.56 x 2.76 in)	
Weight	807 g (1.78 lb)	
Package Contents	Z3Cam-4M camera and 12V Power Supply	

# 4K IP STREAMING



**\*\*Contact Z<sup>3</sup> Technology for Customized Product Options** sales@Z3technology.com +1.402.323.0702 www.Z3technology.com



Copyright 2022 Z3 Technology, LLC. Sony is a registered trademark of Sony Corporation. ZEUS is a registered trademark of Z3 Technology, LLC.