



**Materials & Finishes - Standard:**

- **Pregalvanized (PG):** Conforms to ASTM A653 SS GR 33, G90.
- **Unistrut Defender (DF):** Conforms to ASTM A1046 SS GR 33
- **Hot Dip Galvanized (HG):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM A123
- **Perma-Green (GR):** Steel conforms to ASTM A1011 SS GR 33, E-Coat finish
- **Perma-Gold (ZD):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM B633, Type II SC3
- **Plain (PL):** Conforms to ASTM A1011 SS GR 33

Part No.	Length (ft)	Finish	Product Weight / Ft (lbs/ft)
A3300	20	PG	0.78
A3300	10	PG	0.78
A3300	20	GR	0.78
A3300	10	GR	0.78
A3300	10	PL	0.78
A3300	20	PL	0.78

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** ASTM A240, Type 304 \*
- **Stainless Steel, Type 316 (ST):** ASTM A240, Type 316 \*
- **Aluminum (EA):** ASTM B221, Type 6063-T6 (Extruded) \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Beam Loading - A3300						
Span (in)	Max Allow. Uniform Load (lbs)	Deflection at Uniform Load (in)	Uniform Loading at Deflection			Lateral Bracing Reduction Factor
			Span/180 (lbs)	Span/240 (lbs)	Span/360 (lbs)	
18	420	0.07	420	420	320	1.00
24	320	0.12	320	270	180	1.00
36	210	0.26	160	120	80	0.97
48	160	0.47	90	70	50	0.94
60	130	0.75	60	40	30	0.91
72	110	1.09	40	30	20	0.89
84	90	1.42	30	20	10	0.87
96	80	1.88	20	20	10	0.85

Refer to the General Specifications for loading information.

Column Loading - A3300					
Unbraced Height (in)	Allowable Load at Slot Face (lbs)	Max Column Load Applied at C.G.			
		K=0.65 (lbs)	K=0.80 (lbs)	K=1.0 (lbs)	K=1.2 (lbs)
18	1,430	4,490	4,210	3,860	3,550
24	1,370	4,090	3,750	3,310	2,680
36	1,190	3,390	2,680	1,820	1,260
48	900	2,380	1,600	1,020	KL/r>200
60	680	1,550	1,020	KL/r>200	KL/r>200

Refer to the General Specifications for loading information.

**Project:**

**Architect / Engineer:**

**Date:**  **Phone:**

**Contractor:**

**Address:**

**Notes:**

**Approval Stamp:**