



**Materials & Finishes - Standard:**

- **Pregalvanized (PG):** Conforms to ASTM A653 SS GR 33, G90.
- **Unistrut Defender (DF):** Conforms to ASTM A1046 SS GR 33
- **Hot Dip Galvanized (HG):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM A123
- **Perma-Green (GR):** Steel conforms to ASTM A1011 SS GR 33, E-Coat finish
- **Perma-Gold (ZD):** Steel conforms to ASTM A1011 SS GR 33, Finish conforms to ASTM B633, Type II SC3
- **Plain (PL):** Conforms to ASTM A1011 SS GR 33

Part No.	Length (ft)	Finish	Product Weight / Ft (lbs/ft)
P1001B	10	PG	3.78
P1001B	20	PG	3.78
P1001B	10	HG	4.028
P1001B	20	HG	4.028
P1001B	20	GR	3.78
P1001B	10	GR	3.78
P1001B	10	PL	3.78
P1001B	20	PL	3.78

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** ASTM A240, Type 304 \*
- **Stainless Steel, Type 316 (ST):** ASTM A240, Type 316 \*
- **Aluminum (EA):** ASTM B221, Type 6063-T6 (Extruded) \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

<b>Project:</b>	<input style="width: 90%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 90%;" type="text"/>		
<b>Date:</b>	<input style="width: 15%;" type="text"/>	<b>Phone:</b>	<input style="width: 25%;" type="text"/>
<b>Contractor:</b>	<input style="width: 90%;" type="text"/>		
<b>Address:</b>	<input style="width: 90%;" type="text"/>		
<b>Notes:</b>	<input style="width: 90%;" type="text"/>		

**Approval Stamp:**