



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	Finish	Product Weight / Piece (lbs)
P1204	2-3/8" (60)	6"(152)	HG	1.198
P1204	2-3/8" (60)	6"(152)	GR	1.13
P1204	2-3/8" (60)	6"(152)	SS	1.13
P1205	4-3/8" (111)	8" (203)	EG	1.64
P1205	4-3/8" (111)	8" (203)	HG	1.738
P1205	4-3/8" (111)	8" (203)	GR	1.64
P1205	4-3/8" (111)	8" (203)	SS	1.64
P1206	6-3/8" (162)	10 (254)	EG	2.16
P1206	6-3/8" (162)	10 (254)	HG	2.29
P1206	6-3/8" (162)	10 (254)	GR	2.16
P1207	8-3/8" (213)	12 (305)	HG	2.83
P1207	8-3/8" (213)	12 (305)	GR	2.67
P1208	10-3/8" (264)	14 (356)	HG	3.371
P1208	10-3/8" (264)	14 (356)	GR	3.18

<b>Project:</b>	<input style="width: 100%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 100%;" type="text"/>		
<b>Date:</b>	<input style="width: 25%;" type="text"/>	<b>Phone:</b>	<input style="width: 50%;" type="text"/>
<b>Contractor:</b>	<input style="width: 100%;" type="text"/>		
<b>Address:</b>	<input style="width: 100%;" type="text"/>		
<b>Notes:</b>	<input style="width: 100%;" type="text"/>		

**Approval Stamp:**