



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Nom. Pipe Size	A	D	Finish	Flange Thickness	Product Weight / Piece (lbs)
P1272S	Up to 3/4"	1/4" (6)	3/8"-16 x 1-1/2"	EG	Up to 3/4" (Up to 19mm)	0.39
P1272S	Up to 3/4"	1/4" (6)	3/8"-16 x 1-1/2"	HG	Up to 3/4" (Up to 19mm)	0.413
P1272S	Up to 3/4"	1/4" (6)	3/8"-16 x 1-1/2"	GR	Up to 3/4" (Up to 19mm)	0.39
P1985S	Up to 3/4"	3/8" (10)	1/2"-13 x 1-1/2"	EG	Up to 3/4" (Up to 19mm)	0.62
P1985S	Up to 3/4"	3/8" (10)	1/2"-13 x 1-1/2"	HG	Up to 3/4" (Up to 19mm)	0.657
P1985S	Up to 3/4"	3/8" (10)	1/2"-13 x 1-1/2"	GR	Up to 3/4" (Up to 19mm)	0.62
P1986S	7/8" to 2"	3/8" (10)	1/2"-13 x 1-1/2"	EG	7/8" to 2" (2mm - 51mm)	0.83
P1986S	7/8" to 2"	3/8" (10)	1/2"-13 x 1-1/2"	HG	7/8" to 2" (2mm - 51mm)	0.88
P1986S	7/8" to 2"	3/8" (10)	1/2"-13 x 1-1/2"	GR	7/8" to 2" (2mm - 51mm)	0.83

Project:

Architect / Engineer:

Date:

Phone:

Contractor:

Address:

Notes:

Approval Stamp: