



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	C	Finish	Product Weight / Piece (lbs)
P1546	45°	3" (76)	2-5/16" (59)	EG	0.58
P1546	45°	3" (76)	2-5/16" (59)	DF	0.615
P1546	45°	3" (76)	2-5/16" (59)	HG	0.615
P1546	45°	3" (76)	2-5/16" (59)	GR	0.58
P1546	45°	3" (76)	2-5/16" (59)	ZD	0.58
P1546	45°	3" (76)	2-5/16" (59)	SS	0.58
P1546	45°	3" (76)	2-5/16" (59)	AL	0.23
P2094	82-1/2°	3-9/16" (91)	1-11/16" (43)	EG	0.58
P2094	82-1/2°	3-9/16" (91)	1-11/16" (43)	HG	0.615
P2094	82-1/2°	3-9/16" (91)	1-11/16" (43)	GR	0.58
P2094	82-1/2°	3-9/16" (91)	1-11/16" (43)	ZD	0.58
P2095	75°	3-9/16" (91)	1-11/16" (43)	EG	0.58
P2095	75°	3-9/16" (91)	1-11/16" (43)	HG	0.615
P2095	75°	3-9/16" (91)	1-11/16" (43)	GR	0.58
P2096	67-1/2°	3-1/2" (89)	1-3/4" (45)	EG	0.58
P2096	67-1/2°	3-1/2" (89)	1-3/4" (45)	HG	0.615
P2096	67-1/2°	3-1/2" (89)	1-3/4" (45)	GR	0.58
P2096	67-1/2°	3-1/2" (89)	1-3/4" (45)	ZD	0.58
P2097	60°	3-3/8" (86)	1-7/8" (48)	EG	0.58
P2097	60°	3-3/8" (86)	1-7/8" (48)	HG	0.615
P2097	60°	3-3/8" (86)	1-7/8" (48)	GR	0.58
P2097	60°	3-3/8" (86)	1-7/8" (48)	ZD	0.58
P2097	60°	3-3/8" (86)	1-7/8" (48)	SS	0.58
P2098	52-1/2°	3-1/4" (83)	2-1/16" (52)	EG	0.58
P2098	52-1/2°	3-1/4" (83)	2-1/16" (52)	HG	0.615
P2098	52-1/2°	3-1/4" (83)	2/11/16" (52)	GR	0.58
P2098	52-1/2°	3-1/4" (83)	2/11/16" (52)	ZD	0.58
P2099	37-1/2°	3-1/2" (89)	1-13/16" (46)	EG	0.58
P2099	37-1/2°	3-1/2" (89)	1-13/16" (46)	HG	0.615
P2099	37-1/2°	3-1/2" (89)	1-13/16" (46)	GR	0.58
P2099	37-1/2°	3-1/2" (89)	1-13/16" (46)	ZD	0.58
P2099	37-1/2°	3-1/2" (89)	1-13/16" (46)	AL	0.23
P2100	37-1/2°	2-11/16" (68)	2-5/8" (67)	EG	0.58
P2100	37-1/2°	2-11/16" (68)	2-5/8" (67)	HG	0.615
P2100	37-1/2°	2-11/16" (68)	2-5/8" (67)	GR	0.58
P2100	37-1/2°	2-11/16" (68)	2-5/8" (67)	ZD	0.58

**Project:**

**Architect / Engineer:**

**Date:**  **Phone:**

**Contractor:**

**Address:**

**Notes:**

**Approval Stamp:**