



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Nom. Pipe Size	O.D. Size	Finish	Product Weight / Piece (lbs)
P1563	3/8" (10)	0.675" (17.1)	EG	0.27
P1564	1/2" (13)	0.840" (21.3)	EG	0.29
P1565	3/4" (19)	1.050" (26.7)	EG	0.3
P1566	1" (25)	1.315" (33.4)	EG	0.31
P1567	1-1/4" (32)	1.660" (42.2)	EG	0.38
P1568	1-1/2" (38)	1.900" (48.3)	EG	0.4
P1569	2" (51)	2.375" (60.3)	EG	0.47
P1570	2-1/2" (64)	2.875" (73.0)	EG	0.66
P1571	3" (76)	3.500" (88.9)	EG	0.78
P1572	3-1/2" (89)	4.000" (101.6)	EG	0.87
P1573	4" (102)	4.500" (114.3)	EG	0.9

<b>Project:</b>	<input style="width: 100%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 100%;" type="text"/>		
<b>Date:</b>	<input style="width: 25%;" type="text"/>	<b>Phone:</b>	<input style="width: 25%;" type="text"/>
<b>Contractor:</b>	<input style="width: 100%;" type="text"/>		
<b>Address:</b>	<input style="width: 100%;" type="text"/>		
<b>Notes:</b>	<input style="width: 100%;" type="text"/>		

**Approval Stamp:**