


## P2231A, P2232A



Safety Factor - 21/2

Part	"A"	Wt/100 pcs	Vertical (	Channel	Uniform Design Load
Number	In (mm)	Lbs (kg)	Part No.	Gauge	Lbs (kN)
P2231A	6 152	<b>191</b> 86.6	P1000	12	1,600 (7.12)
			P1100	14	1,200 (5.34)
			P2000	16	800 (3.56)
P2232A	<b>12</b> 305	<b>292</b> 132.4	P1000	12	800 (3.56)
			P1100	14	600 (2.67)
			P2000	16	400 (1.78)

Standard Dimensions for 15/8" (41mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: \(^9\)\(^6\)\(^1\) (14mm); Hole Spacing - From End: \(^{13}\)\(^6\)\(^1\)\(14mm); Hole Spacing - On Center: \(^{17}\)\(^1\)\(14mm); Width: \(^{15}\)\(^1\)\(14mm); Thickness: \(^{17}\)\(16mm)\)

Note: When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

## **MATERIAL**

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

## **FINISHES**

Fittings are available in:

Perma-Green III (GR),

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and

Plain (PL).

Project:		Approval Stamp:		
Date:	Phone:			
Contractor:				
Notes 1:				
Notes 2:				