



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Nom. Pipe Size	A	B	Finish	Product Weight / Piece (lbs)
P2494L	12" (305)	12" (305)	3-7/16" (87)	HG	1.611
P2494L	12" (305)	12" (305)	3-7/16" (87)	GR	1.52
P2494R	12" (305)	12" (305)	3-7/16" (87)	HG	1.611
P2494R	12" (305)	12" (305)	3-7/16" (87)	GR	1.52
P2495L	14" (356)	14" (356)	3-15/16" (100)	HG	1.834
P2495L	14" (356)	14" (356)	3-15/16" (100)	GR	1.73
P2495R	14" (356)	14" (356)	3-15/16" (100)	HG	1.834
P2495R	14" (356)	14" (356)	3-15/16" (100)	GR	1.73
P2496L	16" (406)	16" (406)	4-7/16" (113)	HG	2.37
P2496L	16" (406)	16" (406)	4-7/16" (113)	GR	2.23
P2496R	16" (406)	16" (406)	4-7/16" (113)	HG	2.364
P2496R	16" (406)	16" (406)	4-7/16" (113)	GR	2.23
P2496R	16" (406)	16" (406)	4-7/16" (113)	PL	2.23
P2497L	18" (457)	18" (457)	4-15/16" (125)	HG	2.65
P2497L	18" (457)	18" (457)	4-15/16" (125)	GR	2.66
P2497R	18" (457)	18" (457)	4-15/16" (125)	HG	2.65
P2497R	18" (457)	18" (457)	4-15/16" (125)	GR	2.66
P2498L	20" (508)	20" (508)	5-7/16" (138)	GR	3.08
P2498R	20" (508)	20" (508)	5-7/16" (138)	HG	3.26
P2498R	20" (508)	20" (508)	5-7/16" (138)	GR	3.08
P2499L	22" (559)	22" (559)	5-15/16" (151)	HG	3.66
P2499L	22" (559)	22" (559)	5-15/16" (151)	GR	3.55
P2499R	22" (559)	22" (559)	5-15/16" (151)	HG	3.66
P2499R	22" (559)	22" (559)	5-15/16" (151)	GR	3.55

Project:	<input style="width: 100%;" type="text"/>		
Architect / Engineer:	<input style="width: 100%;" type="text"/>		
Date:	<input style="width: 25%;" type="text"/>	Phone:	<input style="width: 50%;" type="text"/>
Contractor:	<input style="width: 100%;" type="text"/>		
Address:	<input style="width: 100%;" type="text"/>		
Notes:	<input style="width: 100%; height: 30px;" type="text"/>		

Approval Stamp: