


P2513 THRU P2516



When installed in
inverted position use
60% of loads shown.

Part	"A"	Wt/100 pcs	Vertical (_	Uniform Design Load
Number	_In <i>(mm)</i> _	Lbs (kg)	Part No.	_Gauge_	Lbs (kN)
P2513	6 152	161 73.0	P1000	12	1,200 (5.34)
			P1100	14	800 (3.56)
	102		P2000	16	600 (2.67)
	12 305	261 118.4	P1000	12	600 (2.67)
P2514			P1100	14	400 (1.78)
			P2000	16	300 (1.33)
	40	361 163.7	P1000	12	400 (1.78)
P2515 18 457	. •		P1100	14	270 (1.20)
	103.7	P2000	16	200 (.89)	
P2516	24 610	461 209.1	P1000	12	300 (1.33)
			P1100	14	200 (.89)
			P2000	16	150 (.67)

Safety Factor 2½

Standard Dimensions for 15/8" (41mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: \(^9\)\(^8\)\(^1\) (14mm); Hole Spacing - From End: \(^{13}\)\(^8\)\(^1\)\(14mm); Hole Spacing - On Center: \(17\)\(^1\)\(14mm); Width: \(15\)\(^1\)\(14mm); Thickness: \(^{14}\)\(16mm) \\
Note: When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

MATERIAL

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

FINISHES

Fittings are available in:

Perma-Green III (GR),

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and

Plain (PL).

Project:		
	Phone:	
Contractor:		
Notes 1:		
Notes 2:		