UNISTRUT





Materials & Finishes - Standard:

- Base Metal: Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
 Electrogalvanized (EG): Conforms to ASTM B633, Type III SC1
 Unistrut Defender (DF): Conforms to ASTM A1059
 Hot Dip Galvanized (HG): Conforms to ASTM A123 or A153
 Research Conforms to ASTM A123 or A153

- Perma-Green (GR): Conforms to commercial standards for powder coating
 • Perma-Gold (ZD): Conforms to ASTM B633, Type II SC1 or SC3
- Plain (PL): No finish

Materials & Finishes - Special Metals:

- Stainless Steel, Type 304 (SS): Conforms to ASTM A240 or A276, Type 304
- Stainless Steel, Type 316 (ST): Conforms to ASTM A240 or A276, Type 316
- Aluminum (AL): Conforms to ASTM B209, Type 1100F or 5052-H32

Part No.	A	Finish	Product Weight / Piece (lbs)
P2513A	6"(152.4)	HG	1.707
P2513A	6"(152.4)	GR	1.61
P2514A	12" (304.8)	HG	2.767
P2514A	12" (304.8)	GR	2.61
P2515A	18" (457.2)	HG	3.827
P2515A	18" (457.2)	GR	3.61
P2515A	18" (457.2)	SS	3.61
P2516A	24" (609.6)	HG	4.887
P2516A	24" (609.6)	GR	4.61

Project:	
Architect / Engineer:	
Date:	Phone:
Contractor:	
Address:	
Notes:	

Approval Stamp:

^{*} These materials have different physical properties and performance characteristics. Please contact us for design support.