



**Materials & Finishes - Standard:**

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1 or SC3
- **Plain (PL):** No finish

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 \*
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 \*
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	A	B	Finish	Product Weight / Piece (lbs)
P2547	15" (381.0)	8-3/4" (222)	HG	4.45
P2547	15" (381.0)	8-3/4" (222)	GR	4.2
P2548	21" (533.4)	8-3/4" (222)	HG	6.66
P2548	21" (533.4)	8-3/4" (222)	GR	6.28
P2549	27" (685.8)	11-1/4" (286)	HG	9.12
P2549	27" (685.8)	11-1/4" (286)	GR	8.6
P2550	33" (838.2)	11-1/4" (286)	HG	10.71
P2550	33" (838.2)	11-1/4" (286)	GR	10.1
P2551	39" (990.6)	16" (406.4)	HG	13.32
P2551	39" (990.6)	16" (406.4)	GR	12.57

<b>Project:</b>	<input style="width: 100%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 100%;" type="text"/>		
<b>Date:</b>	<input style="width: 25%;" type="text"/>	<b>Phone:</b>	<input style="width: 50%;" type="text"/>
<b>Contractor:</b>	<input style="width: 100%;" type="text"/>		
<b>Address:</b>	<input style="width: 100%;" type="text"/>		
<b>Notes:</b>	<input style="width: 100%; height: 30px;" type="text"/>		

**Approval Stamp:**