Complete Fly Banner Drop Pack



Description:

Complete Fly Banner Drop pack, with everything you need for assembly and display. Includes:

- Flag printed on 100% polyester fabric (115 g/m²), available in various sizes. It offers different spaces for customisation with your choice of colours and/or designs.
- Aluminium and fibreglass flagpole, available in various sizes.
- Base chosen from the options available.

Designed for both indoor and outdoor use.

Technical Data Sheet

Feature	Description
Flag (Included)	Drop tipe
	100% polyester fabric.
	Flag: 115 g/m². Weave: 50% weft and 50% warp.
	Sewn in double backstitch with special thread for outdoor use.
	Double fold hem, 10 mm wide.
	Symmetrical 7 mm double stitching (1.5 mm from edges).
	Stitch width: 5 mm.
	Reinforced with a strip of black plain-weave fabric (width: 30 mm), which acts as a sleeve.
	Water-resistant and wind-resistant. Colourfast and washable.
	Anti-pollution surface treatment.
	Materials: aluminium (10 mm thick) and fibreglass segments.

Flagpole diameter according to the model:

Diameter of the tip (top): 3 mm for all models.

S, M, L: 17,5 mmXL, XXL: 22,5 mm

Colour: black.

Flagpole (Included)

Model	Height	Dimensions of the flag	
S	245 cm	75 x 194 cm	
M	300 cm	92 x 228 cm	
L	350 cm	103 x 298 cm	
XL	440 cm	132 x 352 cm	
XXL	540 cm	145 x 446 cm	

Dimensions					

Base included in the pack. Compatible bases:

- Cross base with weighted ring.
- Screw/threaded base.
- Base for car wheel.
- Pointed base.
- Wall-mount base.
- Water base.
- Deluxe base.
- Base for gazebo foot

Customisable flag colours and designs.

Printing

Other

Inkjet sublimation printing in CMYK (four-colour process) on one side with 94% colour transfer using official inks.

Colour and design

Base (Included)

Weight

Between 2 kg and 7 kg, depending on the base chosen.

Oxford carrying case (120 x 16 cm).

Accessories available (not included).

Loose Fly Banner flag.

Accessories (not included)

Complete pack with everything you need for assembly and display. For both indoor and outdoor use. Reinforced at junction points.

Easy to assemble (less than 5 minutes) and transport.