




12' X 15'

Steel Garage

ASSEMBLY MANUAL



MODEL#: LGCF1683

Missing part? Damaged? Contact us via email at

service@domioutdoorliving.com

www.domioutdoorliving.com

© Copyright 2023–2025 domi LLC. All Rights Reserved.



PLAN AHEAD

Before beginning installation, check local building codes regarding footings, location and other requirements.

Study and understand this instruction.

Important information and helpful tips will make your installation easier and more enjoyable.

Tools and Materials: There are some basic tools and materials you will need for the installation. Decide which method of anchoring and the type of foundation you wish to use in order to form a complete list of the materials you will need.

BEFORE YOU BEGIN

Assembly Instruction: Instructions are supplied in this manual and contain all appropriate information for your installation. Review all instructions before you begin, and during assembly, follow the step sequence carefully for correct results.

Parts List: Check to be sure that you have all the necessary parts and quantities in your package. These are packaged within the carton. Note that extra fasteners have been supplied for your convenience.

Explosion Diagram: All parts except screws and bolts are shown in this diagram, review all parts before you begin. Familiarize yourself with the hardware and fasteners for easier use during installation.

Pre-assembly



1. Two or more people are required for assembly.



2. You will need one or more stepladders.



3. Wearing protective gloves is recommended.



4. You may need a safety hat.



5. Please use a Phillips screw driver.



6. For ease of construction, you may need a drill.



7. You may need a safety goggle.



8. Do not fully tighten screws prior to complete assembly.

Warning & Attention

-Try to assemble this product on the flat ground, otherwise it is difficult to carry out;

-It would be much easier to assemble the product with three or more people;

-Gaskets must be used.

-After assembly, please check whether all screws are tightened, to prevent parts from falling apart.

▲ Use bolts to secure the frame to the ground to against the strong wind.



Please stand inside the shed frame when installing the panels for convenience.


ASSEMBLY TIPS & TOOLS

Watch the Weather Closely: Be sure the day you choose to install your building is dry and calm. Do **NOT** attempt to assemble your building on a windy day. Be careful on wet or muddy ground.

Use Teamwork: Two or more people are required to assemble your building. One person can hold the parts or panels in place while the other person fastens them together and handles the tools. This makes the process of assembling your building faster and safer.


Tools and Materials: Here is a list of some basic tools and materials you will need to assemble your building. Decide which method of anchoring and the type of base you will use to make a complete list of the materials you will need.

WHAT YOU NEED




- Work Gloves
- Safety Glasses
- Step Ladder
- No. 2 Phillips Screwdriver (Magnetic Tip Preferred)
- Utility Knife or Scissors
- Pliers
- Carpenter's Level
- Tape Measure

RECOMMENDED TIME SAVERS



- Power Drill (Cordless, Variable Speed)
- Nut Driver or Wrench
- Square
- String (for squaring the frame)
- Awl (to align holes)

BASE PREPARATION TOOLS



- Lumber and/or Concrete
- Hammer and Nails
- Spade or Shovel
- Hand Saw or Power Saw


How to Select and Prepare Your Building Site: Before you start to assemble your building, you will want to decide on a good location. The best location is a level area with good drainage.

- Allow enough working space so it is not difficult to move parts into position for assembly. Be sure there will be enough space at the entrance for the doors to completely open. Also, there needs to be enough space outside the building to be able to fasten the panel screws from the outside.
- Before assembling any parts, your base should be constructed and an anchoring system should be ready to use.

SAFETY PRECAUTIONS...

*Safety precautions **MUST** be followed at all times throughout the construction of your building!*

sharp edges




Care must be taken when handling various pieces of your building since many contain sharp edges. Please wear work gloves, eye protection and long sleeves when assembling or performing any maintenance on your building.

no children or pets at worksite




Keep children and pets away from the worksite during construction and until the building is completely assembled. This will help avoid distractions and any accidents which may occur.

don't focus weight on roof



NEVER concentrate your weight on the roof of the building. When using a step ladder make sure that it is fully open and on even ground before climbing on it.

always practice proper tool safety





Practice caution with the tools being used in the assembly of this building. Be especially familiar with the operation of all power tools.

beware of wind











Do NOT attempt to assemble your building on a windy day. The large panels can catch the wind like a "sail", causing them to be whipped around making construction difficult and unsafe.




Do NOT attempt to assemble your building before double checking that you have all the parts indicated in the parts lists as well as all hardware. Any building left partially assembled may be seriously damaged by even light winds.




















Garden shed
LGCF1683
12'X15'






















 573 A1—x1		 573 A2—x1	
 1814 A3—x1		 1814 A4—x1	
 1564 A5—x1		 1564 A6—x2	
 1564 A7—x1		 1500 A8—x2	
 1240, 5 A9—x2		 A10—x5	 A11—x4
 A12—x1	 A13—x6		







 2016, 5 B1—x1	 2016, 5 B2—x1	 2015 B3—x1	 2015 B4—x1	 2004 B5—x1	 2004 B6—x1	 2019 B7—x2
 1996 B8—x4	 1844 B9—x4			 1900 B10—x2		
	 B11—x8			 550 B12—x2		
	 B13—x4			 B14—x4		
	 B15—x2	 B16—x14		 B17—x2		

 1792 C1—x1	 1792 C2—x1	
 1792 C3—x1	 1792 C4—x1	
 1552 C5—x1	 1532 C6—x2	
 1552 C7—x1	 1500 C8—x2	
 C9—x6	 C10—x4	 C11—x1
 1813 D1—x2	 1813 D2—x2	
 D3—x2	 D4—x2	 D—x4
 1568 E1—x2	 1568 E2—x2	
 1500 E3—x2	 600 E4—x4	 600 E5—x2
 1555 F1—x2	 1555 F2—x2	
 1474,5 F3—x2		
 G—x4	 G1—x16	 543 G2—x2
 916 G3—x2	 1673 G4—x1	
 443 G5—x1	 400 G6—x1	
 1516 G7—x3	 1473 G8—x2	




			1960	K2—x2		
			1960	K1—x2		
	1967	J8—x2		1641, 5	K3—x2	
	1967	J7—x2		1641, 5	K4—x2	
	1967	J6—x2		1500	K5—x2	
	1967	J5—x2		K—x2		K6—x4
	1967	J4—x2		K7—x2		K8—x2
	1967	J3—x2		1000	L—x2	
	1967	J—x4		1375	L1—x2	
	1967	J2—x2		L3—x3		L4—x110
	1967	J1—x2				

Front Door M				Side Door N			
 1981 M1—x2	 1981 M2—x1	 1981 M3—x1	 1981 M4—x6	 1950 N1—x1	 1950 N2—x1	 1950 N3—x1	 1950 N4—x2
 1204 M5—x1				 661 N5—x2			
 1204 M6—x1				 661 450 N6—x1			
 1204 M7—x2							
 600 1204 M8—x2				 668 N7—x1			
 P—x6		 P1—x6		 Q—x2		 Q1—x2	
 R—x2				 R1—x2			

	M5x8	1# — x8
	M5x10	2# — x16
	M6x12	3# — x88
	M6x16	4# — x4
 		5# — x4
	ST3.5x16	6# — x8
  	M4x6	7# — x170
  	M4x8	8# — x34
  	M4x10	9# — x24
	M4x8	10# — x60
 	M4x8	11# — x28
  	M4x8	12# — x24
 	4x10	13# — x393
	4x20	14# — x74
	4x22	15# — x36
 	4x16	16# — x52
 	4x12	17# — x235
 Gloves  Allen Key  Hole Position Correction Drill  Screwdriver		

The Base For Your Building



Concrete Slab


The slab should be at least 4" (10,2 cm) thick. It must be level and flat to provide good support for the frame.

Prepare the Site/Construct a Base



1. Dig a square, 6" (15,2 cm) deep into the ground (remove grass).
2. Fill up to 4" (10,2 cm) in the square with gravel and tamp firm.
3. Cover gravel with a sheet of 6 mil plastic.
4. Construct a wood frame using four planks of 2x4 (38 mm x 89 mm) lumber.
5. Pour in concrete to fill in the hole and the frame giving a total of 4" (10,2 cm) thick concrete. Be sure surface is level.

Note: Before beginning construction, check local building codes regarding footings, location and other requirements.


Base Frame Dimension



1683(12X15)-Chassis dimensional drawing.



①: Use the part#A10 to connect the bottom frame respectively, and then screw with bolt #13 and gaskets as shown.



②: Insert part #A11 to the corners. Fix with 4 bolts #13 & gaskets.

B8—x4
B9—x4
B10—x2

B11—x8



B12—x2



M6x12

3# — x80



B13—x4




B14—x4


B9

B12


B9



③



①




B12

Total 2 components


①: Use Bracket #B12 to connect 2 Support #B9, and secure with 8 bolts #3.

③: Attach Bracket #B11 to both sides of part #B9 & B8, secure each side with 4 bolts #3.


Repeat the above procedures to assemble another set.



②: Attach Bracket #B13 & #B14 to both sides of part #B9 & B10, secure each side with 4 bolts #3. Repeat the above procedures to assemble another set.



G8—x2



G1—x4



4x12 17# — x8

G8

Insert #G1 into #G8 and secure with 2 screws #17 and gaskets.
Repeat the above procedures to assemble another set.

17#

17#

Insert

G1

G1

G8




G1



B16—x8






4x12 17# — x40




①: Use 8 bolts #17 and 2 Bracket #B16 to secure #B8 to the base frame.

②: Use 2 bolts # 17 to connect the support tube #G8 to #B8. Repeat the above procedures to assemble the other sides.



Insert Bracket #G1 and secure with 2 screws #17 and gaskets for each connection as shown.
Install Bracket #G at the corners and secure with 4 screws #17 and gaskets for each corner as shown.






A9—x2




A12—x1



M5x8 1# — x8



 B1—x1	 B2—x1	 B15—x2	 M5x10 2# — x4	 M6x12 3# — x8	 4x12 17# — x8
---	---	--	--	---	--




Insert Bracket #B15 into Base Frame #A1 and secure with 2 bolts #3. Install A9 (pay attention to the direction). Install #B1, align the holes and secure with 2 bolts #2 and 2 bolts #3 as shown.

FRONT SIDE


Repeat the above procedures to assemble #B2 with Base Frame #A2.

As shown in the box, the wider side of part #A12 is facing outward.



already assembled

Install part #G2 & G7(already assembled in page 05), securing with 2 screws #17 for each connection. Repeat the above procedures to assemble another side.



4x12



17# — x24




B16—x4




B7—x2


FRONT SIDE




BACK SIDE

①: Install #B7 and connect it to the bottom frame by using 2 Brackets #B16, securing with 8 screws #17. Repeat the above procedures to assemble another side.










already assembled



②, ③, & ④: Use screws #17 to install part #G3 & G7, G4 to the frame (make sure the holes on the support tubes are facing outward).








①: Install #B5 and connect it to the bottom frame using B16, securing with 2 bolts and nuts #12 and 2 screws #17.

②: Use 2 Bolts #12 to install #G5 to #B5.


③: Use 2 Screws #17 to install #G3 to #B7. Make sure the holes on the support tubes are facing outward.




OUTSIDE VIEW



INSIDE VIEW




INSIDE VIEW









FRONT SIDE

BACK SIDE




Use 4 screws #17 to secure Wall panel # H and H1 to the support tube #G3 & G5.
 Use 8 screws #13 to secure Wall panel # H and H1 to the base frame #A3 & A7.
 Wall Panel #H1 is wrapped on the outside of #H.
 #B5 is wrapped on the outside of #H1






①: Install #B6 and connect it to the bottom frame using B16, securing with 2 bolts and nuts #12 and 2 screws #17.


②: Use 2 Bolts and nuts #12 to install one side of #G6 to #B6; Use 2 Screws #17 to install another side of #G6 to #B8. Make sure the holes on the support tubes are facing outward.



OUTSIDE VIEW


INSIDE VIEW






Use 2 screws #17 to secure Wall panel # H to the support tube #G6.

Use 4 screws #13 to secure Wall panel # H to the base frame. #B6 is wrapped on the outside of #H.







H—x1 H2—x1

13# — x7
17# — x3

INSIDE VIEW




Use 3 screws #17 to secure Wall panel # H and H2 to the support tube #G3 & G7.

Use 7 screws #13 to secure Wall panel # H and H2 to the base frame #A4 & A6 .



Wall Panel #H2 is wrapped on the outside of #H.

FRONT SIDE



SECTION VIEW

BACK SIDE



①: Install #H and #B3 to #B1, align the holes and secure with 2 screws #11 (One screw #11 at the top and one at the bottom).

#B3 is wrapped on the outside of Wall Panel #H.

Use 4 screws #17 to secure Wall panel # H and H2 to the support tube #G2 & G7.

Use 8 screws #13 to secure Wall panel # H and H2 to the base frame #A1 & A6.

Wall Panel #H2 is wrapped on the outside of #H.


②: Install #H and #B4 to #B2, align the holes and secure with 2 screws #11 (One screw #11 at the top and one at the bottom).

#B4 is wrapped on the outside of Wall Panel #H.

Use 4 screws #17 to secure Wall panel # H and H1 to the support tube #G2 & G7.


Use 8 screws #13 to secure Wall panel # H and H2 to the base frame #A2 & A5.

Wall Panel #H1 is wrapped on the outside of #H.



H3—x1


H4—x1



H6—x1



H7—x1



H8—x1


6# — x8

13# — x8


17# — x4

Use 4 screws #17 to secure Wall panel # H3 and H4 to the support tube #G7.

Use 8 screws #13 to secure Wall panel # H and H2 to the base frame #A6.






FRONT SIDE




BACK SIDE

Side Window Assembly:
Insert part #H6 to the
wall panel #H3/H4 (from
outside to inside), place
transparent board #H8,
align the holes and use 8
screws #6 to fix part #H7
& part #H6 (from inside
to outside).






H-x5



H5-x1


13# - x23

17# - x12





Use 12 screws #17 to secure 5 Wall panels #H and 1 Wall panel #H5 to the support tube #G8 & G7.
Use 23 screws #13 to secure 5 Wall panels #H and 1 Wall panel #H5 to the base frame #A5 & A8.

FRONT SIDE





BACK SIDE

C1—x1  C2—x1 
 C3—x1  C4—x1 
 C9—x2  C11—x1  4# — x2  13# — x39  16# — x12



SECTION VIEW




SECTION VIEW


Top Frame Assembly

Connect part #C1 & #C2, insert part #C9 & #C11 on the inside of part #C1/C2, align the holes and fix with 6 screws 16# and gaskets.
 Connect part #C3 & #C4, insert part #C9 on the inside of part #C3/C4, align the holes and fix with 6 screws 16# and gaskets.

- ①&②: Install the Top Frame C1, C2, C9, and C11 (already assembled) onto the front side, securing with screws #13 and 2 bolts #4.
- ③: Install the Top Frame C3, C4, and C9 (already assembled) onto the back side, securing with screws #13 .



SECTION VIEW





C7-x1
N7-x1
12#-x4



C10-x1
13#-x9

16#-x4
17#-x4

B17-x2




INSIDE VIEW




①: Use 4 screws #17 to install 2 Bracket #B17 below #C7.

②: Clip C7 into the top of H/H1. Use 4 screws #16 and Bracket #C10 to connect top frame #C7 & C3.



③/④: Use 2 bolts and nuts #12 to secure Bracket # B17 to #B5/B6.





⑤: Use 6 screws #13 to secure top frame #C7 with H/H1.

⑥: Use 3 screws #13 to secure #N7 with #C7.





C6—x1

C10—x1


13# — x11

16# — x4



①: Place top frame #C6 on the side wall, use 4 screws #16 and Bracket #C10 to connect top frame #C4 & C6.


②: Use 11 screws #13 to secure top frame #C6 with side panel #H2, H3 & H4.






C5-x1

C6-x1






C10-x2



R-x2

13# - x22

16# - x8




Place top frame #C5 on the side wall, use 4 screws #16 and Bracket #C10 to connect top frame #C2 & C5.


Use 10 screws #13 to secure top frame #C5 with side panel.

Repeat above procedures to connect top frame #C1 & C6.

Use screws #13 to install Windbreak rope hook #R to each side wall as shown.



FRONT SIDE





C8—x2




C9—x4



13# — x30




16# — x24


**INSIDE VIEW**

Install top frame #C8 and #C9 as shown.

Align the holes, use 6 screws #16 to secure top frame C8 & #C9 with side wall (from inside to outside).




Use 15 screws #13 to secure top frame #C8 with side wall (from outside to inside).

**BACK SIDE****FRONT SIDE**






Centre Beam Assembly:

Use the connectors #E4 & E5 to connect E1/E3/E2 as shown in the box.
Secure each connection with 12 screws #9 gaskets and nuts.





SIDE VIEW

Use 8 screws #17 to secure each connection (from bottom to top).





①: Install the centre beam, securing with 4 screws #17.

① 17# — x8







BOTTOM VIEW







Note the orientation of D3 and D4 during installation.




 8# — x4
 13# — x24





①-1
 Insert the centre beam and
 secure with bolts and nut #8.



①-2




②







1 F1-x2
1 F3-x2


F2-x2
7# - x8
17# - x16




Make sure the notch faces outward.



Adjust the Base Frame



Before installing the ground fixing bolts, adjust the angle of the base and the wall to a rectangle: diagonal a-a=b-b.






A13—x6



2# — x12





5# — x4




P—x6





10# — x18





①: You need to prepare expansion bolts by yourself to secure the base frame to the ground.





②: Before installing the drywall anchor, it is necessary to punch holes in the ground. Use 4 Screws #5 to secure #A9 to the ground.
 ③: Install the Front Door hinges.







Install part #K2 to the one side of part #J2 with 5 bolts 7# gaskets and nuts.
 Install part #K1 to the one side of part #J1 with 5 bolts 7# gaskets and nuts.




Adjust the top frame



Attention: The roof panels can be installed in order or reverse order.
If there is a deviation between the roof panels and the top frame installation hole, it is generally caused by the diagonal size deviation of the top frame. The diagonal distance of the top frame be measured and adjusted.



 Please stand inside the shed frame when installing the panels for convenience.






Install roof panel #J1 & J2.



①: Use 6 screws #14 to secure 6 black rubber #L4 and roof panels to the centre beam.

(Make sure the large end of black rubber facing upwards).




Repeat the above procedures to assemble another side.






②: The roof panel J1/J2 is fixed with top frame D1/D2 by using 8 bolts #7, gaskets and nuts.
Repeat the above procedures to assemble another side.



③: Black rubber #L4 shall be inserted at the gap between roof panels and side top beam, then fix with 2 screws #15 to prevent rainwater intrusion. (Place the rubber under J1 and J2, with the large end facing down). Repeat the above procedures to assemble another side.




④: The roof panel is fixed to the side top frame by using 6 screws #13.








TOP VIEW

Diagram of the installation location of the roof panels.
Please stand inside the shed frame when installing the panels for convenience.


Install the roof panels while covering with #L/L1 /L3 as you can.





L4-x32
 15# - x32

L4-x62
 14# - x62



①: Use 62 screws #14 to secure 62 black rubber #L4 and roof panels to the centre beam.

(Make sure the large end of black rubber facing upwards).

②: The roof panels are fixed to the side top frame by using 62 screws #13.

③: Black rubbers #L4 shall be inserted at the gap

between roof panels and side top beam, then fix with 32 screws #15 to prevent rainwater intrusion. (Place the rubber under the roof panels, with the large end facing down).

④: Use 12 bolts #8, gaskets and nuts to fix part #L/L1 /L3 to the roof top. (part #L/#L1 should cover on part#L3).

Pay attention to the installation direction of #L.


⑤: Use 4 bolts #8, gaskets and nuts to fix part #L with roof panel #J1/J2 and part #D1/D2.

K3-x2
K4-x2
K5-x2



K-x2
K7-x2

K6-x4
K8-x2

7# - x90
8# - x8
17# - x4



⑤: Use 37 bolts #7, gaskets and nuts to fix part #K3, K4 & K5 on the cornice of roof panel.
Repeat the above producers to assemble the another side.







④: Use 4 bolts bolts #7, gaskets and nuts to cover part #K6 on the connection of part #K3 & K5/ part #K5 & K4.
Repeat the above producers to assemble the other 3 sides.


②/③: Install part #K7/K8 to 4 corners of the roof, fix with 2 bolts #8, gaskets And nuts.

Repeat the above producers to assemble the other 3 corners.


①: Use 2 screws #17 to install part #K as shown.




Front Door Assembly (Right Side)



BACK SIDE




FRONT SIDE



M1—x1

M4—x3

M3—x1




M8—x1



10# — x4



11# — x8




FRONT SIDE



BACK SIDE

①



FRONT SIDE


10#

M8

BACK SIDE

10#

②



M3

M3

M4

M4

M4

M1

M1

10#

10#

11#

11#

11#

11#

10#

10#

10#

10#

11#

11#

11#

11#


10#

10#


SIDE VIEW

FRONT SIDE






SIDE VIEW




BACK SIDE




FRONT SIDE




Front Door Assembly (Left Side)



BACK SIDE




FRONT SIDE



M2—x1

M4—x3

M1—x1




M8—x1



10# — x4




11# — x8



FRONT SIDE

BACK SIDE


①



FRONT SIDE

BACK SIDE

②



SIDE VIEW

FRONT SIDE

SIDE VIEW









M5—x1
M6—x1

R1—x1


10# — x8
7# — x8

BACK SIDE


FRONT SIDE







Side Door Assembly



BACK SIDE



FRONT SIDE





N5—x2



10# — x8



7# — x8









Q—x1



Q1—x1

BACK SIDE

FRONT SIDE







P1—x6



10# — x6



12# — x12





Front Door M (There is a latch on the left door/There is a handle on the right door) & Side Door #N Assembly:

①: Use 2 Bolts #10 to secure the hinge to the door frame.

②: Use 2 Bolts #12, gaskets and nuts to secure the hinge and Lining board #P1 to the door frame.






(Lining board #P1 is on the inside of the door frame).



①/②: Insert the latch and lock the left door.


③: Open the door: insert the key, rotate 180 counterclockwise, and rotate the handle counterclockwise to open the door.

Lock the door: close the door, insert the key, rotate the handle clockwise, then rotate the key 180 clockwise and pull the key out.





Use Windbreak rope hook #R to fix the door when opening.





Thanks for your purchase.

At domi outdoor living, we believe in our products.

That's why we provide a 12-month warranty and friendly, easy-to-reach after-sales service. So, if you have any questions about our product or assembly, please feel free to contact us. We are here for you.

Support:



After-sales contact email:

service@domioutdoorliving.com

Please have your order ID available if you reach out for support.

If you have damaged parts or product, please send us photos for an immediate response.