





KLASSIC TAILLIGHT KIT FOR 2015+ INDIAN SCOUTS & 2016+ SCOUT

INCLUDED COMPONENTS:

- | | | |
|----------------|------------------|-----------------------|
| (1) Bracket | (1) Light Module | (10) Zip Ties |
| (2) LED lights | (1) Hardware Kit | (1) Instruction Sheet |

QUESTIONS?

-  **EMAIL:**
info@getklocked.com
-  **CALL:** (605) 996.3700

Note: Removal of the rear fender may aid in ease of installation, but it is not required





1. Protect painted surfaces.
2. To remove the stock fender:
 - a. Remove the seat by lifting the nose of the seat and slide the seat backward off the mount
 - b. Remove the four rear fender fasteners(1)
 - c. Remove the rear light harness from the stud under the right side of the fender (do not cut the zip tie)(2)
 - d. Cut the zip tie holding the harness to the license plate bracket.
 - e. Disconnect the 6-place rear lighting connector (3)



3. Remove the stock tail light
 - a. Remove zip ties and unplug the taillight wiring (taillight, turn signals, license plate light) (4)
 - b. Disconnect the stock taillight connector from its anchor (5)




4. Drill out the three stock taillight mount holes to 9/32" (7)
5. Install the provided grommet into the wiring hole in the bracket (8)
6. Install the provided taillights onto the bracket using the 1/4-20 hex bolts in the kit. (9)
7. Run the taillight wiring through the grommet installed in step 5 (10)
8. Install the light assembly onto the fender making sure the stock taillight gasket is still in place. (11)
9. Install the license plate assembly onto the studs and install the provided 1/4-20 lock nuts finger tight




- c. Remove the three lock nuts that attach the license plate assembly and taillight to the fender (6)
- d. Remove the license plate assembly and taillight and set aside, but keep the taillight gasket in place


CAUTION: Klock Werks cannot be held responsible for any damage to painted surfaces during removal or addition of Klock Werks parts.




10. Install the lighting module:
- a. Ground the ring terminal to one of the license plate bracket studs **(12)**
 - b. Plug in the lighting components to the module (they are color coded)
 - c. Tuck the wiring back into the license plate bracket and secure using the provided zip ties **(13)**



11. Torque the three lock nuts installed in step 9 to secure the light assembly to the fender



12. Reinstall the fender and reattach the taillight wires to the fender and module connector **(14)**



13. Reinstall the seat and check taillight function



NOTE: This module corrects the load from the provided lights through the electrical system ensuring no error codes or light pulsing



14.