

SPECIFICATIONS

TEAM6™

UNIVERSAL RAPID SIX BANK CHARGER



| | | |
|-----|--|---|
| 1.0 | DESCRIPTION..... | 3 |
| 2.0 | ELECTRICAL..... | 3 |
| 2.1 | POWER..... | 3 |
| 2.2 | OUTPUT CHARGING CURRENT..... | 3 |
| 3.0 | FEATURES..... | 3 |
| 3.1 | <i>Fully automatic - microprocessor controlled.....</i> | 3 |
| 3.2 | <i>LED Display.....</i> | 3 |
| 3.3 | <i>Advanced detection circuitry and LED indicates battery Real-time conditions.....</i> | 3 |
| 3.4 | <i>Suitable for Ni-CD, Ni-MH and Li-ion batteries.....</i> | 3 |
| 3.5 | <i>Interchangeable cups to mix your radio types, wide range of adapter cups available.....</i> | 3 |
| 3.6 | <i>Battery voltage from 3.6V to 10.8V.....</i> | 3 |
| 3.7 | <i>Interchangeable cups.....</i> | 3 |
| 3.8 | <i>Anodized aluminum casing.....</i> | 3 |
| 3.9 | <i>Warranty</i> | 3 |
| 4.0 | ENVIRONMENT..... | 3 |
| 4.1 | TEMPERATURE..... | 3 |
| 4.2 | HUMIDITY..... | 3 |
| 5.0 | MECHANICAL..... | 4 |
| 5.1 | <i>Plastic Case.....</i> | 4 |
| 5.2 | <i>Physical Size.....</i> | 4 |
| 5.3 | <i>Packaging content.....</i> | 4 |
| 5.4 | <i>PCB material.....</i> | 4 |
| 5.5 | <i>PCB Assembly according IPC-610 class.....</i> | 4 |
| 5.6 | <i>Weight.....</i> | 4 |
| 6.0 | User Guide..... | 5 |
| 7.0 | Troubleshooting tips..... | 6 |

1.0 DESCRIPTION

RAPID Universal tri-chemistry charger.

2.0 ELECTRICAL

2.1 POWER

100-240 V, 50/60 Hz self-switching

2.2 OUTPUT CHARGING CURRENT

Normal Charge Current: 1000mA

Max: 2500mA

Trickle: 50mA

3.0 FEATURES

3.1 Fully automatic - microprocessor controlled.

3.2 Energy efficiency VI power supply.

3.3 LED Display

LED Indicator Status

| LED | Indicator Status |
|-------|------------------|
| RED | Charging |
| GREEN | Charged |

3.4 Advanced detection circuitry with LEDs indicate battery real-time conditions.

3.5 Suitable for Ni-CD, Ni-MH and Li-ion batteries.

3.6 Battery voltage from 3.6V to 10.8V.

3.7 Interchangeable pods

3.8 Anodized aluminum casing.

3.9 One Year Warranty

4.0 ENVIRONMENT

4.1 TEMPERATURE.

a. Ambient Temperature: 32F-104F

4.2 HUMIDITY.

a. Relative Humidity: 20% ~ 90%

5.0 MECHANICAL

- 5.1 Plastic Case: UL plastic material PC+ABS type GE C2950 compatible. Surface texture code is YS9294. Color: black RAL 9005. 6.2
- 5.2 **Physical Size:** 16.54" x 5.5" x 3.35"
- 5.3 Packaging content: TEAM6+power supply+ AC power cable
- 5.4 PCB material should be FR4
- 5.5 PCB Assembly according IPC-610 class
- 5.6 Weight about: 4.4 lbs



16.54"W x 5.5"D x 3.35"H

6.0 USER GUIDE

PLEASE read carefully before using your charger

NOTES:

1. When first powering on the charger, a red light stays on for about 3 seconds while registering the circuits.
2. While charging devices, the RED LIGHT remains on.
3. When fully charged, the GREEN LIGHT turns on.
4. When no device is in a pod, there is no LED light.
5. If you swap pods from the charger, please power the charger off while performing this task.
6. Please only attempt to charge the correct OEM battery and device.

1) Pod Installation.

If the pods are not already installed, simply align the pod with the cavity in the Team6 charger. Press the pod gently into a fully seated position and use a hand screwdriver (Do Not Use Power Tools) to secure the pod into place. Do not over tighten or you could break the pod.



2) Insert the DC cable into the DC port and turn on the switch.



- 3) The unit will perform a self diagnosis indicated by RED LED lights flashing once.
- 4) Insert a battery, or radio with battery attached, into the charger cup.
- 5) The red LED light will illuminate indicating the charge cycle has begun.
The red light will stay illuminated until the charge cycle is complete at which point the green LED light will illuminate indicating that the battery is fully charged.
- 6) Remove the battery/radio for use.

7.0 Troubleshooting tips

“The charger does not power up when plugged in.”

Ensure that the power switch is turned on;

Check that power cables are inserted firmly into cable ports and that the power to the wall plug is on.

“LED light is flashing red.”

This indicates a fault with the battery. Check the bay using another battery. If the bay operates correctly, the battery is not charging sufficiently and will need to be replaced.

“LED lights up red then green, then off.”

Some Li-Ion batteries have internal protection breakers that send a message to the charger to turn off when the battery is fully charged. The battery will be charged and ready for use. If the battery is left in the unit for an extended period, the charge level of the battery will decrease and the charger will recommence charging. To restart charging cycle, attach battery to radio, power radio for minimum of 5 minutes and then reinsert battery. The charge cycle will re-commence.

“One (or more) bay(s) is not working, the LED lights are not illuminating at all.”

To determine if the fault is in the charger or just the pod, remove the cup from the non-working bay and swap it with a cup in a bay that is working correctly. If the same bay LED is still not illuminating then there is likely a fault with the micro-processor in the charger unit. If the faulty bay has moved to the bay that was previously working, the pod is probably defective.