

MELSTONE SERIES

DOUBLE DECK ELECTRIC PIZZA OVEN

MS35E-2

MS38E-2

MS47RE-2

MS47DE-2







FEATURES

- The Pegasus Double Deck Ovens are reliable and versatile solutions designed for professional baking applications.
- Each oven chamber features refractory baking deck with an 8" deck height.
- Choose from four different deck areas and overall oven widths (35", 38", or 47") to suit your needs.
- The series is constructed with heavy duty angle iron frame, which is fully welded to allow for double-stacking.
- Oven exteriors are all heavy duty stainless steel and are fully insulated for cooler outer temperatures and consistent interior temperatures.





- Electric-operated oven with thermostatic temperature control.
- 11.4, 15, 30 kW Electric Power.
- Up to: 752 °F temperature range.
- 24" x 24", 36" x 24", 27" x 27", 36" x 36" interior baking compartment.
- Refractory baking bedplate.
- 8" (203 mm) deck height.
- All stainless steel interior and exteriors.
- Oven door with tempered door.
- Rear electrical connection.
- Fully insulated throughout.
- One year limited warranty (USA & Canada only).

DOUBLE DECK ELECTRIC PIZZA OVEN





TOP VIEW



FRONT VIEW



SIDE VIEW



TECHNICAL SPECIFICATIONS:

	MS35E-2	MS38E-2	MS47RE-2	MS47DE-2
Power	11,280 W	15,000 W	15,000 W	15,000 W
Voltage	208 V	208 V	208 V	208 V
Phase	3P (field convertible to 1P)	3P (field convertible to 1P)	3P (field convertible to 1P)	3P (field convertible to 1P)
Nominal Amps (208V - 3P)	32A (16A + 16A)	42A (21A + 21A)	42A (21A + 21A)	42A (21A + 21A)
Nominal Amps (208V - 1P)	55A (27.5A + 27.5A)	72A (36A + 36A)	72A (36A + 36A)	72A (36A + 36A)
Deck Height	8"	8"	8"	8"
Deck Size	24.4" x 24.0" x 8.0" (620 x 610 x 203 mm)	27.6" x 27.6" x 8.0" (700 x 700 x 203 mm)	36.2" x 24.0" x 8.0" (920 x 610 x 203 mm)	36.2" x 36.2" x 8.0" (920 x 920 x 203 mm)
Decks	2	2	2	2
Thermostat	Up to 752 F	Up to 752 F	Up to 752 F	Up to 752 F
Dimensions (W x H x D)	35.0" x 39.4" x 31.9" (890 x 1000 x 811 mm)	38.0" x 39.4" x 35.4" (965 x 1000 x 898 mm)	46.9" x 39.4" x 31.9" (1190 x 1000 x 811 mm)	46.9" x 39.4" x 43.5" (1190 x 1000 x 1104 mm)
Shipping Dim. (W x H x D)	37.0" x 41.3" x 33.9" (940 x 1050 x 861 mm)	40.0" x 41.3" x 37.3" (1015 x 1050 x 948 mm)	48.8" x 41.3" x 33.9" (1240 x 1050 x 861 mm)	48.8" x 41.3" x 45.4" (1240 x 1050 x 1154 mm)
Ship Wt.	338lb (153 kg)	386 lb (175 kg)	419 lb (190 kg)	552 lb (250 kg)

REQUIRED CLEARANCES:

	Non-Combustible	Combustible
Left	0" (00 mm)	1" (25 mm)
Right	0" (00 mm)	3" (76 mm)
Back	2" (51 mm)	3" (76 mm)



Galaxy Group reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions are nominal.