

FITPRO™ ULTRA V4.11 FIT TEST SOFTWARE

CSA-Z94.4-18

FEATURE UPDATES

Contents

Overview	1
Recording Comfort Assessment and Respirator User Competency Ratings	2
Recording Respirator Comfort Score	2
Recording Respirator User Competency	3
Recording Post-Test Comfort Validation Answer	4
CSA Assessment Display and Reporting	5
Fit Test History Screen	5
Printed Fit Test Report	7
CSA Assessments in Custom Reports	8
Changes to FitPro™ Ultra Database Schema	8
Documentation and Scripts Included with FitPro™ Ultra v4.11 Fit Test Software	8
User Messaging for MS SQL Database Users	

Overview


FitPro™ Ultra (FPU) v4.11 has been updated to record information required by the CSA-Z94.4-18 fit testing standard:

- Pre-test Respirator Comfort Assessment scores can now be recorded.
- Pre-test Respirator User Competency rating can now be recorded.
- Post-test Comfort Validation response can now be recorded.
- The recorded assessment information appears in the fit test records and can be incorporated into custom reports.
- Both passed and failed assessments and fit tests are recorded as required by the standard.



Recording Comfort Assessment and Respirator User Competency Ratings


In the FPU *Assign* screen, fields have been added to record the new CSA information "Respirator Comfort Score" and "Respirator User Competency." Each offers a drop-down style control with appropriate CSA mandated responses available.



Recording Respirator Comfort Score


The *Respirator Comfort Score* lets the person being tested to rate the comfort level of their respirator. The available comfort scores are: "0: No Issues", "1: Discomfort that can be ignored", "2: Some discomfort but still able to function" and "3: UNACCEPTABLE discomfort – not bearable".

The last choice, "N/A: Assessment not recorded", gives the operator the opportunity to opt out of recording the assessment as part of the FPU workflow.



Selecting a score of 0 will allow the operator to proceed to fit testing without further prompting.


Scores of 1 or 2 are not considered a failure by the CSA standard, but FPU will prompt the operator with recommendations to try and improve the score if possible.






If the operator chooses to *Continue*, they will proceed to the fit test screen and be able to perform a fit test. Comfort scores of 0, 1 or 2 will be recorded along with the result of a completed fit test.

If a Respirator Comfort Score of 3 is chosen, this is considered a failure and the operator will not be able to perform a fit test. In this case, they will see a prompt explaining that they can save the record of the failed comfort assessment, or cancel and attempt to improve the score



If the operator chooses to continue and record the failing comfort score of 3 to the FPU database, they will see a message confirming that the Comfort / Competency Assessment failed and that a fit test was not performed.



Recording Respirator User Competency


The Respirator User Competency assessment rates the ability of the person being tested to perform pre-use facepiece inspection, donning, doffing and user seal checks as observed by the fit test operator. This rating is also entered by the operator before a fit test is performed.




The ratings available are "No", the user is not competent, or "Yes", the user is competent. The last choice, "Assessment not recorded" gives the operator an opportunity to opt out of recording the assessment rating as part of the FPU workflow.

Choosing "Yes" allows the operator to proceed to fit testing without further prompts. The "Yes" rating will be recorded along with the results of a completed fit test.

A rating of "No" means the operator has observed that the respirator user is not fully competent at fitting their mask. When a "No" rating is selected, the operator will be prompted whether they want to *Continue* and record the failing assessment rating, or *Cancel* and instruct the user further.




If the operator chooses to continue and record the failing competency rating of "No" to the FPU database, they will see a message confirming that the Comfort / Competency Assessment failed and that a fit test was not performed.




Recording Post-Test Comfort Validation Answer

FPU will prompt the operator at the end of a **PASSING** fit test reminding them to ask the required Comfort Validation question and allowing them to record the response.

The question is to be answered "Yes" or "No" by the respirator user. The last selection, "Assessment not recorded" allows the operator the opportunity to opt out of recording the response as part of the FPU workflow.



The operator must enter a response and click *Continue* to proceed.



Page 4 of 10

The fit test result and the Comfort Validation question response will be saved and the final fit test result will be displayed. Selecting a Comfort Validation Answer of "No" will not result in the fit test being marked as failed; the result of the fit test




is considered independently of a failing Comfort Validation Answer.

CSA Assessment Display and Reporting


When the CSA-Z94.4-18 Protocol is used, the additional comfort and competency information appears in the *Fit Test History* screen, on printed Fit Test Reports and is available for custom reports in the *Reporting* screen.

Fit Test History Screen


In the Fit Test History Detail view, comfort and competency results for CSA protocol fit tests will display the assessment information. For other protocols, that information will be hidden.



If either of the pre-test assessments failed, and a fit test could not be performed, there will not be any fit test result recorded and a message indicating that a fit test was not performed will be shown.



It is possible for the pre-test assessments and fit test to pass, and still record and display a "**No**" response for the final Comfort Validation question.



Printed Fit Test Report


Printed Fit Test Reports also include the assessment information.

	FIT TES	T REPORT	
	04/2	0/2021	
ID NUMBER	1002	Cookies	
LAST NAME	Carlson	New Label	
FIRST NAME	Carter		
COMPANY	Fairview Hospital		
LOCATION	Maplewood		
TEST DATE	04/20/2021 19:52	PORTACOUNT S/N	Test-em-02
DUE DATE	04/20/2023	N95-COMPANION™	Yes
RESPIRATOR	3M 8110S FFP [100] N95	PROTOCOL	CSA-Z94.4-18
MANUFACTURER	3M	PASS LEVEL	100
MODEL	8110S		
RESPIRATOR STYLE	FFP	APPROVAL	84A-0007
RESPIRATOR SIZE	Medium	EFFICIENCY<99%	Yes
COMFORT ASSESSMENT SCORE	0	RESP. USER COMPETENCY	Yes
COMFORT VALIDATION ANSWER	Yes		
EXERCISE	DURATION (sec)	FIT FACTOR	PASS
NORMAL BREATHING	60	123	Yes
DEEP BREATHING	60	99	Yes
TURN HEAD SIDE TO SIDE	60	108	Yes
NOD HEAD UP AND DOWN	60	127	Yes
TALK OUT LOUD	60	118	Yes
BENDING OVER	60	111	Yes
NORMAL BREATHING	60	115	Yes
OVERALL FF		114	Yes
FITTEST OPERATOR		DATE	
	dfg		
NAME		DATE	
	Carter Carlson		
NOTE: none			

	·	EST REPORT	
		4/20/2021	
ID NUMBER	1002	Cookies	
LAST NAME	Carlson	New Label	
FIRST NAME	Carter		
COMPANY	Fairview Hospital		
LOCATION	Maplewood		
TEST DATE	04/20/2021 19:47	PORTACOUNT S/N	Test-em-02
DUE DATE	04/20/2023	N95-COMPANION™	Yes
RESPIRATOR	3M 8110S FFP [100] N95	PROTOCOL	CSA-Z94.4-18
MANUFACTURER	3M	PASS LEVEL	100
MODEL	8110S		
RESPIRATOR STYLE	FFP	APPROVAL	84A-0007
RESPIRATOR SIZE	Medium	EFFICIENCY<99%	Yes
COMFORT ASSESSMENT SCORE	3	RESP. USER COMPETENCY	Yes
COMFORT VALIDATION ANSWER	Not Recorded		
	A fit test w	as not performed	
FITTEST OPERATOR		DATE	
	dfg		
NAME		DATE	
	Carter Carlson	·	
NOTE: none			

CSA Assessments in Custom Reports

The new CSA fields are also available when creating custom Fit Test reports in the *Reporting* screen of FPU.



Changes to FitPro™ Ultra Database Schema

To be able to record the new CSA assessment information, some changes were needed for the FPU database schema. For the default file-based SQLite database type, these changes happen automatically without user intervention. For MS SQL Server databases, the required changes need to be performed manually by a database administrator with sufficient access permission to alter the database schema.

Documentation and Scripts Included with FitPro™ Ultra v4.11 Fit Test Software

Documentation and SQL scripts included with FPU v4.11 instruct existing MS SQL database users on how to update their database schema to the latest schema version (4), and new MS SQL users on how to get started.


User Messaging for MS SQL Database Users

All current MS SQL users that are upgrading to version 4.11 from an earlier version, will see some in-program prompts recommending that they update their database schema. The message informs the user where they can find the documentation for that update. Users can hide the message by choosing,

"DO NOT SHOW THIS WARNING AGAIN".

Database Version Update Recommended In order to take advantage of the latest features of this version of FitPro Ultra, the MS SQL database that is currently in use should be updated. For Canadian users, the main new feature is the ability to capture the Comfort Assessment and Respirator User Competency Assessment information called out in the CSA-Z94.4-18 fit testing standard. If the database update is not performed, this information will not be stored in the database. For all MS SQL users, the length of the "Notes" field for the People and Fit Test records have been expanded from a maximum of 64 characters to a maximum of 128 characters. If neither of these features are important to your application, this message can be safely ignored and your database can be used as it is. For more information and instructions on how to update the database, see the document "MS SQL Server Support README.pdf" found in this folder: "C:\Program Files (x86)\TSI\FitPro Ultra\MS SQL Support" CONFIRM DO NOT SHOW THIS WARNING AGAIN

If an existing MS SQL database is not upgraded and the CSA protocol is used, the options to enter the assessment information will not be available in the *Assign* screen. Those users will see messaging to remind them that updating their MS SQL database would enable these features.





TSI Incorporated – Visit our website **www.tsi.com** for more information.

 USA
 Tel: +1 800 680 1220
 India
 Tel: +91 80 67877200

 UK
 Tel: +44 149 4 459200
 China
 Tel: +86 10 8219 7688

 France
 Tel: +33 1 41 19 21 99
 Singapore Tel: +65 6595 6388

 Germany
 Tel: +49 241 523030

P/N 6015662 Rev. A ©2021 TSI Incorporated Printed in U.S.A.

