



60 Ton Ironworker 230V, 1Ph, with PowerLink

Product Images



Short Description

Edwards 60 Ton Ironworker, JAWS, Dedicated Coper Notcher Station, Hydraulic Accessory Power Pack

Additional Information

Stock Number	ED9-IW60-1P230-A
Amps	23
Angle Shear Max Capacity 1/2"	3 x 3
Angle Shear Max Capacity 3/8"	4 x 4
Angle Shear Max Capacity (In.)	3 x 3 x 1/2, 4 x 4 x 3/8
Angle Shear Work Height (In.)	39-7/8
Coper Notcher Max Capacity (In.)	2 x 4 x 5/16
Coper Notcher Work Height (In.)	39-1/2
Flat Bar Shear Max Capacity 1/2"	12
Flat Bar Shear Max Capacity 3/4"	4
Flat Bar Shear Max Capacity 3/8"	14
Flat Bar Shear Max Capacity (In.)	3/8 x 14, 1/2 x 12, 3/4 x 4
Flat Bar Shear Max Round (In)	7/8
Flat Bar Shear Max Square (In)	7/8
Flat Bar Shear Rating (Tons)	60
Flat Bar Shear Work Height (In.)	34-1/2
Gross Weight (Lbs)	2550
Hydraulic Pump (GPM)	3-1/2
Hydraulic Reservoir (Gal.)	7
Hydraulics (GPM)	3-1/2
Hydraulics (PSI)	2500
Model Number	IW60-1P230-AC500
Motor Amps	23
Motor (HP)	5 HP 1 ~ 230V
Motor Speed (RPM)	1725

Overall Dimensions (L x W x H) (In.)	36-1/8 x 46-1/8 x 56-1/8
Product Dimensions (In.)	46-1/8 x 36-1/8 x 56-1/8
Prop 65	Cancer and Reproductive Harm
Punch Max Capacity (In.)	1 diam. in 3/4 mild steel
Punch Open Height (In)	8-1/8
Punch Rating (Tons)	60
Punch Shut Height (In)	6-7/8
Punch Stroke (In.)	1-1/4
Punch Work Height (In.)	36-9/16
Rating (Tons)	60
Reservoir (Gal.)	7
Shipping Dimensions (L x W x H) (In.)	45 x 51 x 62
Valve Pressure (PSI)	2750
Weight (Lbs.)	2550

