



THE ATACR™ FAMILY OF RIFLESCOPES: SERVING THE FRONT LINE AND THE BLUE LINE.

If there is such a thing as a “professional” rifle scope, it is an ATACR™. They are designed for military, law enforcement, hunters, and other tactical professionals... and for those who simply want to shoot like a professional.

An ATACR™ rifle scope is the combination of the finest materials, engineering expertise, mechanical reliability and optical performance available today. Simply put, there is no expense spared, no detail overlooked in building a Nightforce ATACR™.

They are the basis for our Mil-Spec riflescopes, currently in use by several branches of the U.S. Military and allies around the world.

All ATACR™ riflescopes feature ED glass, which produces brilliant images, superb color contrast, and exceptional resolving power—allowing you to distinguish the smallest targets at extreme distances.

Our higher-power ATACR™ riflescopes, designed for extreme long-range precision, meet or exceed the capability of any known rifle cartridge. Our lower-magnification models provide unmatched versatility in a vast range of shooting environments.

They are an investment in a lifetime of accuracy and reliability.

(continued on back)

1-8x24 F1

Magnification range	1-8x
Focal plane	First
Body tube diameter	34 mm
Overall length	10.1 in/256 mm
Mounting length	5.7 in/144 mm
Weight	21.0 oz/595 g
Click value	.1 MRAD
Internal adjustment range	E: 30 MRAD W: 30 MRAD
Parallax adjustment	Fixed @ 125 m
Eye relief	3.7 in/95 mm
Field of view @ 100 yd/m	1x: 96.1 ft/32.0 m 8x: 13.1 ft/4.4 m
Exit pupil	1x: 11.3 mm 8x: 3.2 mm
Illumination	Daylight visible, externally adjustable, two night vision settings
Elevation feature	Capped, finger-adjustable
Power Throw Lever	Standard
Reticles available	FC-DM ^x ™



4-16x42 F1

Magnification range	4-16x
Focal plane	First
Body tube diameter	34 mm
Overall length	12.6 in/320 mm
Mounting length	6.3 in/160 mm
Weight	30.0 oz/850 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 89 MOA/26 MRAD W: 60 MOA/18 MRAD
Parallax adjustment	45 yd-∞
Eye relief	3.5 in/90 mm
Field of view @ 100 yd/m	4x: 26.9 ft/9.0 m 16x: 6.9 ft/2.3 m
Exit pupil	4x: 10.3 mm 16x: 2.7 mm
Illumination	Digillum™
Elevation feature	ZeroHold®
Power Throw Lever	Standard
Reticles available	MOAR™ MIL-C™ MIL-R™ MIL-XT™ H-59™ TREMOR3™



4-16x50 F2

Magnification range	4-16x
Focal plane	Second
Body tube diameter	34 mm
Overall length	13.1 in/333 mm
Mounting length	6.3 in/161 mm
Weight	33.3 oz/944 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 110 MOA/30 MRAD W: 60 MOA/16.4 MRAD
Parallax adjustment	45 y-∞
Eye relief	3.5 in/89 mm
Field of view @ 100 yd/m	4x: 26.9 ft/9.0 m 16x: 6.9 ft/2.3 m
Exit pupil	4x: 9.5 mm 16x: 3.2 mm
Illumination	Digillum™
Elevation feature	ZeroStop®
Power Throw Lever	Standard
Reticles available	MOAR™ MIL-R™



4-20x50 F1

Magnification range	4-20x
Focal plane	First
Body tube diameter	34 mm
Overall length	13.9 in/353 mm
Mounting length	5.9 in/150 mm
Weight	35.2 oz/998 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 130 MOA/38 MRAD W: 100 MOA/29 MRAD
Parallax adjustment	11 yd-∞
Eye relief	3.5 in/90 mm
Field of view @ 100 yd/m	4x: 23.6 ft/7.9 m 20x: 6.1 ft/2.0 m
Exit pupil	4x: 8.3 mm 20x: 2.5 mm
Illumination	Digillum™
Elevation feature	ZeroStop®
Power Throw Lever	Standard
Reticles available	MOAR™ MIL-C™ MIL-XT™ TREMOR3™



Go to nightforceoptics.com to find a dealer near you.

Nightforce is a registered trademark of Nightforce Optics. © 2020 Nightforce Optics. All rights reserved.

NIGHTFORCE®
RUGGED. RELIABLE. REPEATABLE.

5-25x56 F2

Magnification range	5-25x
Focal plane	Second
Body tube diameter	34 mm
Overall length	14.3 in/363 mm
Mounting length	6.1 in/156 mm
Weight	39.1 oz/1108 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 120 MOA/35 MRAD W: 60 MOA/17 MRAD
Parallax adjustment	45 yd—∞
Eye relief	3.5 in/90 mm
Field of view @ 100 yd/m	5x: 18.0 ft/6.0 m 25x: 4.9 ft/1.6 m
Exit pupil	5x: 10.5 mm 25x: 2.2 mm
Illumination	Digillum™
Elevation feature	ZeroStop®
Power Throw Lever	Standard
Reticles available	MOAR™ MOAR-T™ MIL-R™



5-25x56 F1

Magnification range	5-25x
Focal plane	First
Body tube diameter	34 mm
Overall length	15.4 in/390 mm
Mounting length	5.9 in/150 mm
Weight	37.6 oz/1066 g
Click value	.250 MOA or .1 MRAD
Internal adjustment range	E: 120 MOA/35 MRAD W: 80 MOA/24 MRAD
Parallax adjustment	45 yd—∞
Eye relief	3.5 in/90 mm
Field of view @ 100 yd/m	5x: 18.7 ft/6.2 m 25x: 4.9 ft/1.6 m
Exit pupil	5x: 8.3 mm 25x: 2.3 mm
Illumination	Digillum™
Elevation feature	ZeroStop®
Power Throw Lever	Standard
Reticles available	MOAR™ MIL-C™ MIL-R™ MIL-XT™ H-59™ TREMOR3™



7-35x56 F1/F2

	7-35x56 F1	7-35x56 F2
Magnification range	7-35x	7-35x
Focal plane	First	Second
Body tube diameter	34 mm	34 mm
Overall length	16.0 in/406 mm	16.0 in/406 mm
Mounting length	6.6 in/167 mm	6.6 in/167 mm
Weight	39.3 oz/1113 g	39.3 oz/1113 g
Click value	.250 MOA or .1 MRAD	.250 MOA or .1 MRAD
Internal adjustment range	E: 100 MOA/29 MRAD W: 60 MOA/17 MRAD	E: 100 MOA/29 MRAD W: 60 MOA/17 MRAD
Parallax adjustment	11 yd—∞	11 yd—∞
Eye relief	3.6 in/91 mm	3.5 in/89 mm
Field of view @ 100 yd/m	7x: 15.0 ft/5.0 m 35x: 3.4 ft/1.1 m	7x: 15.0 ft/5.0 m 35x: 3.4 ft/1.1 m
Exit pupil	7x: 6.0 mm 35x: 1.6 mm	7x: 6.0 mm 35x: 1.6 mm
Illumination	Digillum™	Digillum™
Elevation feature	ZeroStop®	ZeroStop®
Power Throw Lever	Standard	Standard
Reticles available	MOAR™ MIL-C™ MIL-R™ MIL-XT™ H-59™ TREMOR3™	MOAR-T™ MIL-C™



NIGHTFORCE®
RUGGED. RELIABLE. REPEATABLE.

Go to nightforceoptics.com to find a dealer near you.

Nightforce is a registered trademark of Nightforce Optics. © 2020 Nightforce Optics. All rights reserved.