



**ADVANCED PHOTONICS**  
**SUPREME-GRADE THERMAL**  
**CLIP-ON SCOPE**  
**TCS-6075-MOD**

The TCS-6075-MOD is the professional-grade thermal clip-on sight for aiming and engagement designed to work seamlessly with a wide variety of firearms and daytime scopes. The TCS-6075-MOD is a plug-and-play unit, deployed in mere seconds with no zeroing needed. It is also a great tool for reconnaissance and tactical surveillance.

The latest generation silent and Auto-NUC sensor is at the base of the TCS-6075-MOD. GSCI proprietary hardware and software solutions are built around the sensor and offer exceptional image quality along with unique tools for added tactical advantage and user safety.

The TCS-7500-MOD is fully dust- and waterproof, meets and exceeds modern standards. It is a robust, reliable tool for long-term, intensive use in any environment, in any lighting or weather conditions.

**HIGH PERFORMANCE CORE**

Shutterless FPA with Auto-NUC technology guarantees a silent, reliable, and most importantly uninterrupted operation of the device.

All TWS models are equipped with 640x480 cores 17 microns and 50 Hz refresh rate.

<i>PERFORMANCE CAPABILITIES: Human (1.7x0.5m)</i>	
Detection: Human (1.7x0.5m)	2500m
Recognition: Human (1.7x0.5m)	935m
Identification: Human (1.7x0.5m)	500m

<i>PERFORMANCE CAPABILITIES: Vehicle (2.3x2.3m)</i>	
Detection: NATO Target (2.3x2.3m)	3382m
Recognition: NATO Target (2.3x2.3m)	1268m
Identification: NATO Target (2.3x2.3m)	675m

**ADVANTAGES OF TCS-6075-MOD**

Ergonomic Full-Size Keypad, User-Friendly Interface

High-Performance, Auto-NUC, Shutterless, Silent FPA, <40mk

Built-In GPS Module (Optional)

Variety Of Clip-On Mounting Options and Weapon Mounts

Battery Compartment with "Quick Swap" Battery Holders Up To 13 Hours Battery Life

External Power and Video-Out Port: Connection to Ultra-Portable Display Unit HMD-800-MOD

Smooth And Precise Focus Adjustment

Multi-Use Picatinny Side Mounting Bracket Can Be Replaced With The GPS Module

Fast Germanium Glass Objective Lens

Canadian-Made, Non-ITAR System

All-Aluminum Rugged Housing



**Designed, Developed, Manufactured by GSCI Advanced Photonics**  
 120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA  
 WWW.GSCI.NET | GSCI@GSCI.NET | +1.905.850.0990

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Co., Inc. Mass of the product represents measurable weight of all components this product consists of, such as optics, mechanics, and electronics. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2022 General Starlight Co., Inc. Canada. All rights reserved.



**ADVANCED PHOTONICS**  
**SUPREME-GRADE THERMAL**  
**CLIP-ON SCOPE**  
**TCS-6075-MOD**

**TECHNICAL SPECIFICATIONS**

<b>MAIN OPTICAL PARAMETERS</b>	
Optical Magnification Clip-On	1X
Objective Lens System	75mm
Field of View	8.3°x6.2°
Focusing Range	3m .. Infinity

<b>THERMAL SENSOR &amp; ELECTRONICS</b>	
FPA Type	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation)
FPA Resolution and Pitch	640x480, 17µm
FPA Sensitivity (NETD)	<40mK
FPA Refresh Rate	50Hz
Digital Zoom	1X, 2X, 4X, 8X
Internal Display	Full Size: 0.6-Inch Diagonal, AMOLED, Colour, 800x600
Imaging Modes	Monochrome (White-Hot / Black-Hot) and Multiple Colour Palettes

<b>ENHANCED VISION &amp; TACTICAL FEATURES</b>	
Digital Passive Stadiametric	Yes
Digital Detail Enhancement Feature (DDE)	Yes
Wide Dynamic Range Feature (WDR)	Yes
Stow Safety Feature (SSF)	Yes
Shot-Initiated FOV Feature (SIF)	Built-In Adjustable Shock Sensor
Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display)	Yes: 3-Axis Sensors - Magnetometer, Accelerometer and Gyroscope
Integrated Compass	Yes
Pitch / Roll / Azimuth Indications	Yes
Digital Video Recorder with Real-Time Stamp	Optional

<b>USER CONVENIENCE FEATURES</b>	
User Profiles (Configurable)	Yes: 8
Real-Time Date-Time Stamp	Yes: Simplified, Extended, DTG Formats
Automatic/Manual Pixel Masking	Yes
Automatic Power Down Control	User-Configurable: 10 .. 60 minutes of inactivity

<b>POWERING OPTIONS &amp; CONSUMPTION</b>	
Accepted Batteries	4 (Four) AA Alkaline / Lithium / Rechargeable
Universal Port	Video-Out, Remote Control and External Power (4VDC .. 15VDC)
Battery Life on 4x AA Lithium	Up to 13 Hours

<b>MECHANICAL &amp; ENVIRONMENTAL PARAMETERS</b>	
Dimensions	225x75x67mm
Weight	680 grams
Environmental Protection	Fully Waterproof, IP67, Nitrogen-Purged
Operating Temperature	-40°C .. +50°C

<b>WARRANTY &amp; EXPORT INFORMATION</b>	
Warranty	7 Years, Limited
Made In Canada	ITAR-Free



DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Co., Inc. Mass of the product represents measurable weight of all components this product consists of, such as optics, mechanics, and electronics. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2022 General Starlight Co., Inc. Canada. All rights reserved.



**ADVANCED PHOTONICS**  
**SUPREME-GRADE THERMAL**  
**CLIP-ON SCOPE**  
**TCS-6075-MOD**

**STANDARD EQUIPMENT**

*WHAT'S IN THE BOX*

1	Thermal Imaging Clip-On Sight
2	Front Lens Protective Cover
3	Rifle Mount: Heavy-Duty MAK-PICATINNY or Dual Lever Adjustable Rifle Mount DLM
4	Built-In Digital Video Recorder GS-DVR-INT (Comes with 32GB microSD card and SD adapter)
5	Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display), 3-Axis Sensors for Compass Reading, Inclinometer/Pitch Reading, and Level/Roll Reading
6	USB Power Cable
7	Video-Out Cable
8	Soft Carrying Pouch
9	User Manual
10	Quick Reference Card
11	7-Year Warranty with Activation Form
12	Waterproof Hard Carrying Case
13	Cleaning Kit (3-in-1 Multi-Pen + Cleaning Cloth)

**OPTIONAL ACCESSORIES**

**Advanced Multi-Functional Laser Rangefinder Unit QRF-4500.** The new advanced LRF unit is the all-in-one laser rangefinder system with increased capabilities featuring built-in GPS module, compass, laser pointer and add-on IR illuminator. It is the indispensable tool with multiple capabilities used for reconnaissance, tactical surveillance, and other scenarios. Its operational capabilities and functionality by far exceed similar systems on the market. The rangefinding module operates at Mil-Standard 1550nm wavelength. Device's compact size allows obstruction free access to controls of the main unit to which the LRF is attached: be it a firearm or an electro-optical system.



**Universal Battery Pack MVP-240.** The MVP-240 is the only high capacity battery pack on the market with 3 power outputs – 3V, 5V and 12V. This battery pack runs off 8 standard, easy-to-find AA batteries with quick swap cartridges. The MVP-240 doubles the operational time.

It can be conveniently mounted on the side of the TWS.

**HMD-800-MOD** is the modernized ultra-portable display unit that streams thermal video directly from the TCS-6075-MOD. HMD-800-MOD helps you observe the surroundings without exposing yourself. It can also be used with a remote control so a user can have control over the system from distance.



**Wired Remote Control TRC-120.** Lightweight and ergonomic, the TRC-120 is instantly paired to the TWS-6050-MOD as soon as you connect both with the cable. With identical, "no-confusion" connectors and cables you can control your device, feed its video signal to an external display or supply power from an external power source.