



elementiu

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

DWS/LF/100

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom. Tel: 0044 (0) 1923 249911

PAGE 1 of 8 MATERIAL SAFETY DATA SHEET

VERSION: 5.1 DIAMOND ABRASIVE LAPPING FLUID

COPIED: NJM

ISSUE DATE: 27^h MAY 2009

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name: Diamond Abrasive Lapping Fluid

Product ref: DWS/LF/100, DWS/LF/250 & DWS/LF/500

Application: Lapping fluid for use with diamond abrasive sharpening stones.

Suppliers trade names: JBMA Diamond Abrasive Lapping Fluid

Engis UK JOKE Hyprez OS Fluid Formulation 990-140/2

Supplier: Engis UK Ltd

9 Centenary Business Park

Station Road

Henley On-Thames

Oxon RG9 1DS

Tel: 0044 (0) 1491 411117 Fax: 0044 (0) 1491 412252

Email: REACH@engis.uk.com

Emergency telephone: 0044 (0) 800 132052

2. HAZARD IDENTIFICATION

Skin: May cause mild skin irritation. Repeated contact may cause

dermatitis.

Eyes: Vapor is irritating to the eyes. Liquid may cause moderate irritation,

redness and tearing.

Inhalation: Drowsiness, dizziness, nasal and respiratory irritation.

Ingestion: Harmful. May cause lung damage if swallowed (chemical

pneumonia).

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom. Tel: 0044 (0) 1923 249911

PAGE 2 of 8 MATERIAL SAFETY DATA SHEET

VERSION: 5.1 DIAMOND ABRASIVE LAPPING FLUID

COPIED: NJM

ISSUE DATE: 27^h MAY 2009

Physical/chemical hazard: Empty containers may contain residues, which can cause an

incendiary discharge.

Fire and explosion hazard: Moderate hazard. Product can release vapors or form flammable

mixtures at temperatures at or above the flashpoint.

Environmental hazard: Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical family: Petroleum Distillate.

Ingredient Name	CAS No.	REACH (EINECS) Reg. No.	Wt (%)	Health (Class)	Risk Phrase (R. No.)
Isoparaffinic Hydrocarbon	64742-47-8	265-149-8	40% - 70%	Xn	R65
Isoparaffinic Hydrocarbon	64742-48-9	265-150-3	20% - 50%	Xn	R65

4. FIRST-AID MEASURES

Skin contact: Wash thoroughly with soap and water. Remove contaminated

clothing and launder before reuse.

Eye contact: Flush thoroughly with water until irritation subsides, lifting upper and

lower lids to facilitate cleansing. If irritation persists, seek medical

assistance.

Ingestion: Do not induce vomiting. Keep person at rest and seek immediate

medical attention.

Inhalation: Remove individual to fresh air. If breathing is difficult, administer

oxygen and seek medical attention.

Trend Machinery & Cutting Tools Ltd. Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom. Tel: 0044 (0) 1923 249911

	WD24 / TR United Kingdom. Tel: 0044 (0) 1923 249911	
	PAGE 3 of 8	MATERIAL SAFETY DATA SHEET
,	VERSION: 5.1	DIAMOND ABRASIVE LAPPING FLUID
,		COPIED: NJM
		ISSUE DATE: 27 ^h MAY 2009

5. FIRE-FIGHTING MEASURES

Extinguishing media: Use water spray to cool surfaces exposed to fire to disperse

vapours and to protect personnel attempting to stop any leakage. Extinguish the fire with foam, dry chemical or carbon dioxide.

Hazardous decomposition

products: Carbon monoxide, carbon dioxide, various oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Eliminate source of ignition.

Prevent liquid from entering sewers, water courses or low areas. Keep personnel/public away. If possible, shut off source of release

without further hazard.

Advise authorities if liquid has entered sewers, water courses or has

contaminated soil.

Clean-up procedures: Contain spilled liquid with absorbent material.

Take up absorbed material and place into suitable container for

disposal.

Consult an expert on disposal of recovered material to ensure

conformity to local regulations.

7. HANDLING AND STORAGE

Storage temperature: Ambient.

Transport temperature: Ambient.

Storage pressure: Atmospheric.

Electrostatic accumulation

hazard: Yes. Use proper grounding procedures for bulk storage.

Materials/coatings

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom, Tel: 0044 (0) 1923 249911

WD2	WD24 / IR United Kingdom. Tel: 0044 (0) 1923 249911	
PAGE 4 of 8	MATERIAL SAFETY DATA SHEET	
VERSION: 5.1	DIAMOND ABRASIVE LAPPING FLUID	
	COPIED: NJM	
	ISSUE DATE: 27 ^h MAY 2009	

compatibility: Glass, carbon steel, stainless steel, polyethylene, polypropylene,

polyester.

Materials/coatings

unsuitable: Strong oxidizing agents (acids), natural rubber, butyl rubber, EPDM,

polystyrene. Testing for compatibility with specific plastic materials

is recommended.

General notes: Keep container closed. Store in well ventilated area away from

incompatible materials. Do not expose liquid or vapours to open flame, heat or sources of ignition. Empty product containers may contain residues (liquid/vapour). Do not re-use containers without

adequate cleaning.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limit (WEL):

systems (liquid or spray) where contact is likely, wear safety glasses with side shields, long sleeves and plastic gloves. Provide sufficient local exhaust and general ventilation to maintain exposure below WEL, especially for spraying operations producing mists. Where

300 ppm for Petroleum Hydrocarbon components. For open

concentrations in air may exceed WEL and the engineering practices are not adequate to accomplish exposure reduction, approved respirators may be necessary to prevent overexposure by

inhalation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Thin liquid.

Odour: Mild, characteristic.

Freezing point: Not determined.

Boiling range: 376°F-483°F (191°C - 251°C).

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom, Tel: 0044 (0) 1923 249911

	VV D2	WD24 / Th Officed Kingdom. Tel: 0044 (0) 1923 249911	
PAGE 5 of 8 MATERIAL SAFETY DATA SHEET		MATERIAL SAFETY DATA SHEET	
	VERSION: 5.1	DIAMOND ABRASIVE LAPPING FLUID	
		COPIED: NJM	
		ISSUE DATE: 27 ^h MAY 2009	

Percentage volatile: 35%.

Specific gravity: 0.8 gm/cc.

Flashpoint ASTM D56: 144°F (63°C).

Auto-ignition temperature: 640°F (338°C).

Viscosity: 4-5 cps.

Evaporation rate: Slower than water.

Solubility in water: Dispersible.

Vapour density: Heavier than air.

10. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure. Hazardous

polymerization will not occur. Not reactive at normal temperatures

and pressures.

11. TOXICOLOGICAL INFORMATION

Target organ effects: Not available.

Development Information: Not available.

Cancer information: Not available.

Other health effects: Not available.

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom. Tel: 0044 (0) 1923 249911

PAGE 6 of 8 MATERIAL SAFETY DATA SHEET

VERSION: 5.1 DIAMOND ABRASIVE LAPPING FLUID

COPIED: NJM

ISSUE DATE: 27^h MAY 2009

12. ECOLOGICAL INFORMATION

Environmental degradability: Based upon data for similar substances or estimated data, this

product is to biodegrade slowly. This product is expected to be

removed in a wastewater treatment facility.

Ecotoxicity: Based upon data for similar substances or estimated data, no acute

toxicity to aquatic organisms is expected at the maximum water solubility of this product. Long term adverse effects to aquatic

organisms are not expected.

13. DISPOSAL CONSIDERATIONS

Product disposal method: Care should be taken to ensure compliance with EC, national and

Local Regulations. This product is not suitable for disposal by landfill, municipal sewers, drains, natural streams or rivers. Waste product must be disposed of via an authorized waster disposal company in accordance with Local and National Waste Disposal

Regulations.

Packaging disposal: Dispose of in accordance with local regulations. Waste codes

should be assigned by the user, preferably in discussion with the

waste disposal authorities.

14. TRANSPORT INFORMATION

Land transport

ADR/RID: Not hazardous. GGVS/GGVE: Not hazardous.

Maritime transport

IMDG: Not hazardous. GGV Sea: Not hazardous.

Air Transport

ICAO: Not hazardous. IATA: Not hazardous.

Odhams Trading Estate, St Albans Road, Watford, Hertfordshire WD24 7TR United Kingdom, Tel: 0044 (0) 1923 249911

WD24 / Th Officed Kingdom. Tel: 0044 (0) 1923 249911		24 7 TH Officed Kingdom. Tel: 0044 (0) 1923 249911
	PAGE 7 of 8	MATERIAL SAFETY DATA SHEET
	VERSION: 5.1	DIAMOND ABRASIVE LAPPING FLUID
		COPIED: NJM
		ISSUE DATE: 27 ^h MAY 2009

15. REGULATORY INFORMATION

Carriage: None.

Classification: Harmful.

Symbol: Xn

Risk phrases: R65: Harmful. May cause lung damage if swallowed.

Safety phrases: S37: Wear suitable gloves.

S51: Use only in well ventilated areas.

S62: If swallowed, do not induce vomiting, seek medical advice

immediately and show the container and label.

UK regulatory references: Control of Substances Hazardous to Health Regulations.

Chemicals (Hazard Information & Packaging for Supply)

Regulations 2002 (CHIP3).

EU directives: Dangerous Preparations Directive 1999/45/EEC. System of specific

information relating to Dangerous Preparations 2001/58/EEC. Registration, Evaluation, Authorisation and restriction of Chemicals

(REACH) EC 1907/2006 Article 31 and Annex II.

Statutory instruments: Control of Substances Hazardous to Health Regulations.

Chemicals (Hazard Information & Packaging for Supply)

Regulations.

Approved code of practice: Compilation of Safety Data Sheets Safety Data Sheets (3rd Edition).

16. OTHER INFORMATION

User notes: Sections revised: - 14, 15, 16

Information sources: Supplier's own safety data sheet, issued 05/26/09 Ref 918 CHIP.

Suppliers MSDS states "Prepared in accordance with the REACH

Competent Authority Information – May 2008".

Tre	Trend Machinery & Cutting Tools Ltd.		
Odhams	Odhams Trading Estate, St Albans Road, Watford, Hertfordshire		
WD24 7TR United Kingdom. Tel: 0044 (0) 1923 249911			
PAGE 8 of 8	MATERIAL SAFETY DATA SHEET		
VERSION: 5.1	DIAMOND ABRASIVE LAPPING FLUID		
	COPIED: NJM		
	ISSUE DATE: 27 ^h MAY 2009		

UK REACH Competent Authority Information Leaflet 13 - REACH

and SDS- May 2008.

Revisions comments: Revision to hazard symbol.

Trend MSDS ref: LEAF/HS/DWSLF

Legal disclaimer: The information provided in this Material Safety Data Sheet is

correct to the best of our knowledge, information and belief at the stage of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This company shall not be held liable for any damage resulting from handling or from contact with the above

product.





elementiu

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

DWS/LF/100

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant