

## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 03/13/2017

Reviewed on 03/13/2017

### 1 Identification

#### Product identifier

**Trade name:** 1101 Osmo Wood Wax Finish Clear Extra Thin

**Application of the substance / the mixture**

Coating compound/ Surface coating/ paint  
Paint

#### Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf

#### Information department:

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

#### Emergency telephone number:

Poison Center Berlin (24 h): +49 (0) 30 / 30686 790 consultation in German and English

### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

#### Label elements

##### GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

##### Hazard pictograms

Void

##### Signal word

Warning

##### Hazard statements

H227 Combustible liquid.

##### Precautionary statements

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P210 Keep away from flames and hot surfaces. – No smoking.

P280 Wear protective gloves / eye protection / face protection.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

##### Additional information:

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

##### Information pertaining to particular dangers for man and environment:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

(Contd. on page 2)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 2)

### 5 Fire-fighting measures

**Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:**

Water with full jet

**Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**Advice for firefighters**

**Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation  
Keep away from ignition sources

**Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

**Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**Protective Action Criteria for Chemicals**

<b>PAC-1:</b>		
34590-94-8	(2-methoxymethylethoxy)propanol	150 ppm
<b>PAC-2:</b>		
34590-94-8	(2-methoxymethylethoxy)propanol	1700* ppm
<b>PAC-3:</b>		
34590-94-8	(2-methoxymethylethoxy)propanol	9900** ppm

### 7 Handling and storage

**Handling:**

**Precautions for safe handling** Keep away from heat and direct sunlight.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 3)

Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.

**Information about protection  
against explosions and fires:**

Keep ignition sources away - Do not smoke.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by  
storerooms and receptacles:**

Store only in the original receptacle.  
Store in a cool location.

**Information about storage in one  
common storage facility:**

Do not store together with alkalis (caustic solutions).  
Do not store together with oxidizing and acidic materials.

**Further information about  
storage conditions:**

Store in cool, dry conditions in well sealed receptacles.  
Keep receptacle tightly sealed.

**Storage class:**

10

**Specific end use(s)**

No further relevant information available.

**8 Exposure controls/personal protection**

**Additional information about  
design of technical systems:**

No further data; see item 7.

**Control parameters**

**Components with limit values that  
require monitoring at the  
workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

**34590-94-8 (2-methoxymethylethoxy)propanol**

PEL	Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
REL	Short-term value: 900 mg/m <sup>3</sup> , 150 ppm Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
TLV	Short-term value: 909 mg/m <sup>3</sup> , 150 ppm Long-term value: 606 mg/m <sup>3</sup> , 100 ppm Skin

**Additional information:**

The lists that were valid during the creation were used as basis.

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 4)

**Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.  
Keep away from foodstuffs, beverages and feed.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

**Breathing equipment:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device only when aerosol or mist is formed.  
Short term filter device:

Filter A/P2

**Protection of hands:**

Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)

**Body protection:**

Protective work clothing

**9 Physical and chemical properties**

**Information on basic physical and chemical properties****General Information****Appearance:**

**Form:** Fluid  
**Color:** Colorless  
**Odor:** Mild

**Change in condition**

**Melting point/Melting range:** Undetermined.

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 5)

<b>Boiling point/Boiling range:</b>	> 180 °C (> 356 °F)
<b>Flash point:</b>	> 62 °C (> 144 °F) (DIN EN ISO 2719)
<b>Ignition temperature:</b>	240 °C (464 °F)
<b>Auto igniting:</b>	Product is not selfigniting.
<b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
<b>Explosion limits:</b>	
<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	7.0 Vol %
<b>Density at 20 °C (68 °F):</b>	0.83-0.87 g/cm <sup>3</sup> (6.926-7.26 lbs/gal)
<b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	>21 mm <sup>2</sup> /s (40 °C)
<b>Solvent content:</b>	
<b>VOC content:</b>	~ 430 g/l / 3.58 lb/gl
<b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

<b>Reactivity</b>	No further relevant information available.
<b>Chemical stability</b>	
<b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
<b>Possibility of hazardous reactions</b>	Reacts with fabric soaked in the product (e.g. cleaning wool).
<b>Conditions to avoid</b>	No further relevant information available.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition products:</b>	Formation of toxic gases is possible during heating or in case of fire. Nitrogen oxides (NO <sub>x</sub> ) Carbon monoxide and carbon dioxide
<b>Additional information:</b>	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

(Contd. on page 7)

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 6)

### 11 Toxicological information

#### Information on toxicological effects

##### Acute toxicity:

##### LD/LC50 values that are relevant for classification:

##### 64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

##### Primary irritant effect:

##### on the skin:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

##### on the eye:

No irritating effect.

##### Sensitization:

Sensitizing effect by skin contact is possible with prolonged exposure.

##### Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

#### Carcinogenic categories

##### IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

##### NTP (National Toxicology Program)

None of the ingredients is listed.

##### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

#### Toxicity

##### Aquatic toxicity:

##### 64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

**Persistence and degradability** No further relevant information available.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 7)

**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

### 13 Disposal considerations

**Waste treatment methods****Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**Uncleaned packagings:****Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agent:** Solvent naphtha

### 14 Transport information

**UN-Number****DOT, ADR, ADN, IMDG, IATA** Void**UN proper shipping name****DOT, ADR, ADN, IMDG, IATA** Void**Transport hazard class(es)****DOT, ADR, ADN, IMDG, IATA**  
**Class** Void**Packing group****DOT, ADR, IMDG, IATA** Void**Environmental hazards:****Marine pollutant:** No**Special precautions for user** Not applicable.**Transport in bulk according to Annex II of****MARPOL73/78 and the IBC Code** Not applicable.**UN "Model Regulation":** Void

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

(Contd. of page 8)

### 15 Regulatory information

*Safety, health and environmental regulations/legislation specific for the substance or mixture*

*Sara*

**Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):**

All ingredients are listed.

**Proposition 65**

**Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**Carcinogenicity categories**

**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

Void

**Signal word**

Warning

**Hazard statements**

H227 Combustible liquid.

**Precautionary statements**

P210 Keep away from flames and hot surfaces. – No smoking.

P280 Wear protective gloves / eye protection / face protection.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 03/13/2017

Reviewed on 03/13/2017

**Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin**

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. of page 9)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** product safety department

**Contact:** Hr. Dr. Starp

**Date of preparation / last revision** 03/13/2017 / 15

**Abbreviations and acronyms:** ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flam. Liq. 4: Flammable liquids – Category 4  
 Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**