# **TIOMOS PCC**

## Pie-cut corner hinge



- For connecting two corner cabinet doors
- For door thicknesses up to 24 mm (factory setting for 19 mm door thickness with cup distance 3.5 mm)
- 35 mm full cup drill hole
- Shallow cup depth of 11.8 mm
- 3-dimensional adjustment with corresponding mounting plate
- Without integrated damper

#### Available in one version:

• Without integrated damper

## ORDER INFORMATION FOR DRILLING PATTERN 45/9.5, NICKEL

Door overlay			Damper		Without	Art. No.		
			With	Without		Click-on for screw fitting	Click-on for press fitting	
1			-	•	-	<b>F045</b> 138 <b>517</b>	<b>F045</b> 138 <b>518</b>	

 $<sup>^{\</sup>mbox{\tiny 1}}$  Cup material: steel, nickel-plated/Arm material: zamak, nickel-plated


#### **PAGE REFERENCES**

Tiomos mounting plates	86
Accessories	96
Technical information	100


Assembly technology	637
Assembly aids	654

#### **PLANNING DIMENSIONS**


All dimensions in millimetres




Door thickness (TS) 14 mm Cup distance (TA) 3.5 mm Mounting plate height 0




Door thickness (TS) 15 mm Cup distance (TA) 3.5 mm Mounting plate height 0




Door thickness (TS) 16 mm Cup distance (TA) 3.5 mm Mounting plate height 0



Door thickness (TS) 19 mm (factory setting) Cup distance (TA) 3.5 mm Mounting plate height 0




Door thickness (TS) 24 mm Cup distance (TA) 3.5 mm Mounting plate height 0



#### Adjustment in the hinge arm:

- Stepless side adjustment ± 2 mm
   Stepless depth adjustment via
- worm screw +3/-2 mm
  3. Door thickness 14-24 mm
  (factory setting 19 mm)

Height adjustment via mounting plate



#### **DRILLING PATTERNS 45/9.5**

# For screw fitting For press fitting

#### **CUP DIMENSIONS**

