



XJ Frame Stiffeners Rear Installation Instructions

Thank you for purchasing our XJ Frame Stiffeners Rear!

Installation Notes:

- This Product is designed to fit Jeep Cherokees 2 door or 4 door 1984-2001.
- During installation some cutting, and grinding may be required depending on the Jeep.
- These Stiffeners are designed to work with our Front and Center stiffeners.
- Refer to the factory service manual on removing any factory components.

Tools required:

- Angle Grinder
- Welder with at least 3/16" capabilities
- Jack and Jack Stands
- C-Clamp
- Hand tools

Contents of kit

Bill of Materials			
QTY	Part Number	Etch Number	Description
1	B4W188767	767 B	XJ Frame Stiffener Rear Front Driver
1	B4W188768	768 B	XJ Frame Stiffener Rear Rear Driver
1	B4W188769	769 B	XJ Frame Stiffener Rear Front Passenger
1	B4W188770	770 B	XJ Frame Stiffener Rear Rear Passenger

Step 1:

Park the Jeep on a level surface and remove the factory rear sway bar, bump stops, rear most exhaust hanger, trailer hitch, and fuel filler neck heat shield.

Step 2:

Install the frame stiffeners on the rail of the Jeep as shown in the picture below and mark where the under coating needs to be removed for welding.



Step 3:

Using the proper tool remove the under coating in the locations marked in step 2.

Step 4:

Reinstall the frame stiffeners starting with front section. Weld the stiffener to the rail of the Jeep the slots are designed to be welded up. On the long weld seams we recommend staggering a 1" weld 1" apart. A C-Clamp and a jack or jack stand can be used to get the stiffeners tight against the rail.

Step 5:

Paint the Frame Stiffeners we recommend using a vehicle under coating to keep from rusting.

Step 6:

Repeat step 1 through step 5 on the opposite side of the jeep.

Step 7:

Reinstall all factory components removed in step 1.

Professional Services Disclaimer:

The content of all pages of this website (collectively, the "Website"), such as text, graphics, images, information and other material (collectively, "Content") is for informational purposes only. Any information furnished on this Website is not intended nor implied to be automotive advice and is not intended to replace personal consultation with a qualified automotive service technician, mechanic, or similar automotive professional.

Barnes 4WD has not examined the Content for accuracy, timeliness, completeness, appropriateness, or helpfulness. Barnes 4WD does not endorse any specific tests, products, procedures, opinions, or other information that may be mentioned on this Website. Your reliance upon information and Content obtained by you at or through this Website is solely at your own risk. IN NO EVENT SHALL BARNES 4WD BE LIABLE OR OTHERWISE RESPONSIBLE FOR ANY DAMAGE OR INJURY (INCLUDING DEATH) TO YOU, OTHER PERSONS, OR PROPERTY ARISING FROM ANY USE OF ANY PRODUCT, INFORMATION, IDEA, OR INSTRUCTION CONTAINED IN THE CONTENT.

BARNES 4WD DOES NOT MAKE ANY REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, AT LAW OR IN EQUITY, WITH RESPECT TO ANY PRODUCT FEATURED ON THE WEBSITE, INCLUDING WITHOUT LIMITATION WITH RESPECT TO MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, VALUE, VALIDITY, OR ENFORCEABILITY, AND ANY AND ALL SUCH OTHER REPRESENTATIONS OR WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED