

**Certification
Issued Under the Authority of the
Federal Communications Commission**

By:

**Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089**

Date of Grant: 06/18/2019

Application Dated: 06/18/2019

**Quanshun Communication Technology Co., Ltd
Quanshun Bldg., Daxiamei, Nan'an,
Quanzhou, Fujian,,
China**

Attention: Roger Chen , Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2ADQZTP4GNX
Name of Grantee: Quanshun Communication Technology Co., Ltd
Equipment Class: PCS Licensed Transmitter held to face
Notes: PTT Network Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	826.4 - 846.6	0.132	2.5 PM	4M16F9W
	24E	1852.4 - 1907.6	0.264	2.5 PM	4M16F9W
	24E	1850.7 - 1909.3	0.256	2.5 PM	1M11G7D
	24E	1850.7 - 1909.3	0.258	2.5 PM	1M10D7W
	24E	1860.0 - 1900.0	0.207	2.5 PM	17M9G7D
	24E	1860.0 - 1900.0	0.209	2.5 PM	17M9D7W
	27	1710.7 - 1754.3	0.203	2.5 PM	1M11G7D
	27	1710.7 - 1754.3	0.282	2.5 PM	1M11D7W
	27	1720.0 - 1745.0	0.189	2.5 PM	17M9G7D
	27	1720.0 - 1745.0	0.208	2.5 PM	17M9D7W
	22H	824.7 - 848.3	0.164	2.5 PM	1M10G7D
	22H	824.7 - 848.3	0.157	2.5 PM	1M11D7W
	22H	829.0 - 844.0	0.134	2.5 PM	8M96G7D
	22H	829.0 - 844.0	0.162	2.5 PM	8M96D7W

Output power listed is ERP for below 1 GHz and EIRP for above 1 GHz. LTE supports 1.4/3/5/10/15/20 MHz BW modes in Band 2/4, and 1.4/3/5/10 MHz BW modes in Band 5. The antenna(s) used for this transmitter must not be co-located with any other transmitters, except in accordance with FCC multi-transmitter product procedures. SAR compliance for body-worn operating conditions is restricted to belt clips, holsters or similar accessories that have no metallic component in the assembly. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR for head (face up) and body-worn accessory transmission exposure conditions are 0.38 W/kg and 1.18 W/kg, respectively.

This device contains functions that are not operational in U.S Territories. This filing is only applicable for US operations.