

MaxiCharger DC Compact

40kW (Max. 47kW)



MaxiCharger DC Compact

Big power and big value in a compact package





Fast and Effective

Built to increase charging efficiency

- Dual-ports provide up to 47kW of power
- Charge 2 vehicles simultaneously
- A 30 min charge equates to 130 km of range



Compact Design

Optimized for any location

- Ultra-compact with big DC power in a small package
- Flexible installation allows for fixed or mobile positioning
- DC Compact has low installation costs, meaning a faster ROI due to reduced capital expenditures for the site operator



Smart Advertising and Communication Platform

Improve your ROI

- User-friendly 21.5-inch LCD touch screen
- Powered by smart operating system, Android 10 with enhanced advertising placements
- Communicate, promote or attract customers generating new revenue streams

A Closer Look at the **MaxiCharger DC Compact**



OCPP1.6/2.0.1



One Stop Cloud **Network Management**





Certified Through a 16-point Inspection Process



ISO 15118 Plug & Charge



Smart Charging



Compatible with CCS2, CHAdeMO



APP, RFID Card, Credit Card, Mobile Payment



Weather Resistant



Technical Specifications

DC Output Connection

Charging mode Mode 4: CCS2

Output power Rated power 40kW (Max. 47kW)

Output voltage 150-950V Max ouput current 133A

Number of outputs 2*CCS2, or 1*CCS2+1*CHAdeMO, or 1*CCS2

Peak efficiency ≥96%

AC Input Connection

Earthing system 3P, N, PE

Input voltage 3-phase 400V AC ±10%

Input frequency50HzPower factor≥0.99Harmonic distortion (THDi)≤5%

General Characteristics

 $\begin{array}{lll} \textbf{IP and IK rating} & \textbf{IP54; IK10} \\ \textbf{Operating altitude} & 2000m \\ \textbf{Operating temperature range} & -30\,^{\circ}\text{C} \sim +55\,^{\circ}\text{C} \\ \textbf{Storage temperature range} & -40\,^{\circ}\text{C} \sim +70\,^{\circ}\text{C} \\ \textbf{Mounting} & \textbf{Pedestal or wheels} \\ \end{array}$

Dimensions (H×W×D) Pedestal or wheels
1000×550×265 mm

User interface

Screen type21.5 inch LCD touch screenCable length4m standard; 5m optional

Status indication LED/LCD/APP

User interface Autel Charge APP; Autel Charge Cloud

Connectivity 4G, Wi-Fi, Ethernet

Communication protocols OCPP 1.6J (Can be upgraded to OCPP 2.0.1 later)

User authentification APP, RFID card

Software update OTA updates via web portal

Certification and standards

Safety and compliance IEC 61851-1; IEC 61851-23; IEC 61851-21-2; ISO 15118 Plug&Charge

EMC compliance CE, EMC Class A

Warranty 24 months, warranty extension possible

AUTEL

Autel Intelligent Technology Corp., Ltd

Phone: +49(0)89 540299608E-mail: evinfo.eu@autel.com

Website: autelenergy.com

Autel Energy









^{*} All pictures shown are for illustration purpose only, actual product and specifications may vary due to product enhancement