



TM

**VENIERI**  
SPA

**PRODUCT  
LINE**

**LOADERS  
TELESCOPIC WHEEL LOADERS  
BACKHOE TOOL CARRIERS**





# Venieri 70

1948-2018

Ferdinando and Carlo Venieri create the first **Venieri crawler tractor**



1948

New fully-equipped plant opens

Started co-operation with **Perkins engine**



1954



1956

Production of **hydrostatic forklift** begins



1960



Production of **earthmoving machines** begins

Venieri became **limited company (L.T.D.)** strengthening his name on the domestic market



1962

1968



Venieri introduces the **world's first hydrostatic transmission** in earthmoving machines

1974

Introduction of a **new type of backhoe loader**



1980



Actual **new plants** open.

1986

Production of the **rigid type** of Backhoe Loader has been **discontinued**

1992



Venieri patented the world's **first electrical backhoe loader**



1999

**Hydrostatic transmission** started to be installed in **all machines**

2002



**100% Green Power Company**



2010

**75 Worldwide Partners**

2012



Venieri introduces **STAGE IV/TIER 4F**



2016

2018



**QUALITY MEETS HISTORY.**

# WHEEL LOADERS



**13.63C**



**10.63D**

<i>Linkage</i>	"Z" BAR	PARALLEL
<i>Engine Max Power</i>	184 HP	143 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	12.000 Kg	8.000 Kg
<i>Static Tipping Load, Full Turn</i>	9.600 Kg	5.200 Kg
<i>Bucket Capacity, Min/Max</i>	2,7 - 3,0 m <sup>3</sup>	1,8 - 2,2 m <sup>3</sup>
<i>Max Permissible Weight</i>	14.150 Kg	10.110 Kg
<i>Tyres</i>	20,5 R25	17,5 x 25
<i>Forks Load Capacity (EN 474-3)</i>	5.600 Kg	3.400 Kg
<i>Max Speed</i>	40 Km/h	40 Km/h



**5.63D**



**4.63H**

<i>Linkage</i>	"Z" BAR	"Z" BAR
<i>Engine Max Power</i>	79 HP	72 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	6.400 Kg	5.600 Kg
<i>Static Tipping Load, Full Turn</i>	4.400 Kg	4.200 Kg
<i>Bucket Capacity, Min/Max</i>	1,1 - 1,5 m <sup>3</sup>	1,0 - 1,5 m <sup>3</sup>
<i>Max Permissible Weight</i>	6.270 Kg	6.200 Kg
<i>Tyres</i>	405/70 R20	16/70 x 20
<i>Forks Load Capacity (EN 474-3)</i>	2.720 Kg	2.560 Kg
<i>Max Speed</i>	40 Km/h	30 Km/h



### **9.63D**

"Z" BAR  
143 HP  
STAGE 5/TIER 4f  
8.600 Kg  
5.500 Kg  
1,8 - 2,2 m<sup>3</sup>  
10.110 Kg  
17,5 x 25  
3.680 Kg  
40 Km/h



### **8.63C HL**

PARALLEL  
128 HP  
STAGE 5/TIER 4f  
9.400 Kg  
4.600 Kg  
1,2 m<sup>3</sup>  
8.750 Kg  
460/70 R24  
2.800 Kg  
40 Km/h



### **2.63D Plus**

"Z" BAR  
53 HP  
STAGE 5/TIER 4f  
5.300 Kg  
3.000 Kg  
0,75 - 1,2 m<sup>3</sup>  
4.800 Kg  
12,0/75 x 18  
1.920 Kg  
28 Km/h



### **2.63D**

"Z" BAR  
53 HP  
STAGE 5/TIER 4f  
4.700 Kg  
2.700 Kg  
0,70 - 1,2 m<sup>3</sup>  
4.800 Kg  
12,0/75 x 18  
1.760 Kg  
20 Km/h



### **1.63D**

"VZPK"  
53 HP  
STAGE 5/TIER 4f  
3.840 Kg  
1.850 Kg  
0,5 - 0,8 m<sup>3</sup>  
3.600 Kg  
12 - 16,5  
1.104 Kg  
40 Km/h

# TELESCOPIC WHEEL LOADERS



## 7.63D

"Z" BAR  
128 HP  
STAGE 5/TIER 4f  
9.100 Kg  
5.000 Kg  
1,4 - 2,0 m<sup>3</sup>  
8.750 Kg  
15,5 x 25  
3.000 Kg  
40 Km/h

## 8.63TL

<i>Linkage</i>	TELESCOPIC ARM
<i>Engine Max Power</i>	143 HP
<i>Engine Emission</i>	STAGE 4/TIER 4f
<i>Maximum Loading Height with Forks - Telescopic Extended</i>	5.280 mm
<i>Bucket Capacity, Min/Max</i>	1,2 m <sup>3</sup>
<i>Max Permissible Weight</i>	9.100 Kg
<i>Tyres</i>	460/70 R24
<i>Forks Load Capacity (EN 474-3)</i>	3.200 Kg
<i>Max Speed</i>	40 Km/h



## 1.33C

PARALLEL  
53 HP  
STAGE 5/TIER 4f  
2.300 Kg  
2.000 Kg  
0,45 m<sup>3</sup>  
4.130 Kg  
12 - 16,5  
1.200 Kg  
20 Km/h



## 1.63D TL

<i>Linkage</i>	TELESCOPIC ARM
<i>Engine Max Power</i>	53 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f
<i>Maximum Loading Height with Forks - Telescopic Extended</i>	3.700 mm
<i>Bucket Capacity, Min/Max</i>	0,5 m <sup>3</sup>
<i>Max Permissible Weight</i>	4.000 Kg
<i>Tyres</i>	31x15,50 - 15,3
<i>Forks Load Capacity (EN 474-3)</i>	1.250 Kg
<i>Max Speed</i>	40 Km/h

# BACKHOE TOOL CARRIERS



## 8.23G



## 10.23E

<i>Linkage</i>	"Z" BAR	"Z" BAR
<i>Engine Max Power</i>	106 HP	106 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f	STAGE 5/TIER 4f
<i>Breakout Force</i>	6.900 Kg	10.800 Kg
<i>Static Tipping Load, Full Turn</i>	5.250 Kg	6.150 Kg
<i>Bucket Capacity, Min/Max</i>	1,1 - 1,4 m <sup>3</sup>	1,3 - 2,0 m <sup>3</sup>
<i>Max Permissible Weight</i>	8.490 Kg	9.920 Kg
<i>Tyres</i>	16/70 x 24	17,5L x 24
<i>Forks Load Capacity (EN474-3)</i>	3.120 Kg	3.880 Kg
<i>Max Speed</i>	40 Km/h	40 Km/h
<i>Max Digging Depth, Std./Telescopic</i>	4,6 - 5,4 m	5,0 - 6,0 m



## 1.33C

<i>Linkage</i>	PARALLEL
<i>Engine Max Power</i>	53 HP
<i>Engine Emission</i>	STAGE 5/TIER 4f
<i>Breakout Force</i>	2.300 Kg
<i>Static Tipping Load, Full Turn</i>	2.000 Kg
<i>Bucket Capacity, Min/Max</i>	0,45 m <sup>3</sup>
<i>Max Permissible Weight</i>	4.130 Kg
<i>Tyres</i>	12 - 16,5
<i>Forks Load Capacity (EN474-3)</i>	1.200 Kg
<i>Max Speed</i>	20 Km/h
<i>Max Digging Depth, Std./Telescopic</i>	2,75 - 3,25 m



**VENIERI** SPA



The illustrations on the present folder do not necessarily show the product standard version. Data and dimensions described in this folder are not binding. Venieri reserves the right of carrying out possible changes at any time and without previous notice because of its policy of steady development and improvement of the products.



[www.vf-venieri.com](http://www.vf-venieri.com)



Via Piratello, 106 - 48022 Lugo (RA) ITALY  
Tel. +39 0545 904411 - Fax +39 0545 30389  
e-mail: info@vf-venieri.com [www.vf-venieri.com](http://www.vf-venieri.com)

**Spare Parts**  
Tel. +39 0545 904429 Fax +39 0545 24555  
e-mail: ricambi@vf-venieri.com