



Product Specification Guide

Product Name: **SYDNEY HARBOUR'S INSTANT RUST CLEAR SEALER**

PRODUCT DESCRIPTION:

Sydney Harbour's Instant Rust Clear Sealer is designed for use when protection, sealing or isolation is required on interior or exterior surfaces that have been finished with Sydney Harbour's Liquid Iron & Instant Rust. Sydney Harbour's Instant Rust Clear Sealer is a water based, non-yellowing, matt polyurethane sealer that is water and stain resistant. Quick drying. Dries to an ultra low sheen finish. Appears milky white in can, dries clear.

Sydney Harbour's Liquid Iron & Instant Rust is an authentic rusted finish. On exterior surfaces this finish will continue to rust after initial application, so be mindful that rust stains (caused by run-off) may appear on adjacent surfaces. To prevent these stains we recommend finishing with Sydney Harbour's Instant Rust Clear Sealer. However, if isolation is not required, Sydney Harbour's Liquid Iron & Instant Rust should be left to weather and age.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 6.58 g/L VOC.

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

It is designed for use over interior or exterior surfaces finished with Sydney Harbour's Liquid Iron and Instant Rust that require sealing or isolation. Coating with Instant Rust Clear Sealer can slow or stop further rusting, therefore preventing rust staining on adjacent surfaces caused by water run-off.

COLORS:

Appears milky white in can, dries clear.

LIMITATIONS:

Please note that once Instant Rust Clear Sealer has been applied, no further oxidation will occur to the Liquid Iron & Instant Rust.

Not suitable for use other than that intended. For example, this product is not suitable as a clear sealer for Sydney Harbour's Liquid Copper and Patina Green.

Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

PREPARATION:

Apply Sydney Harbour's Liquid Iron and Instant Rust according to specification. When the desired level of rust/oxidation has occurred, rinse surface with clean water to remove any Instant Rust residue and allow to dry completely. Allow a minimum of 48 hours drying and curing/hardening time prior to the application of Sydney Harbour's Instant Rust Clear Sealer.

If Liquid Iron surface is not rinsed and thoroughly dried as directed, Instant Rust Clear Sealer may dry with a milky appearance.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush or spray, ensuring even distribution. Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. If applying more than 2-3 coats, a low sheen appearance will result. Do not apply coats too thick – two thin to moderate coats is sufficient. Applying thick coats may cause the finish to dry with a milky appearance. It is important that good coverage is achieved and there are no areas where the product is not completely applied. It is recommended recoating be carried out every 12 months.

COVERAGE RATES:

Covers approximately 600 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates.

CLEAN UP:

Water.

COMPLEMENTARY PRODUCTS:

Sydney Harbour's Instant Rust Clear Sealer has been designed for use over Sydney Harbour's Liquid Iron & Instant Rust only.

PACKAGING:

Sydney Harbour's Instant Rust Clear Sealer is available in Quart and Gallon sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

MANUFACTURER/DISTRIBUTOR DETAILS:

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: admin@shpcompany.com

Web: www.SHPCcompany.com