



Product Specification

Product Name: **SYDNEY HARBOUR'S PALM BEACH BLACK**

PRODUCT DESCRIPTION:

Sydney Harbour's Palm Beach Black is a water based, colorfast black stain for most timber types. Palm Beach Black will produce a transparent effect to enhance the grain of timber. This stain is made with the highest quality UV resistant exterior grade pigments that will enhance water resistance and UV protection.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 42.6 g/L VOC.

- Southern California Air Quality Management District Rule 314 compliant
- LEED v4 & v4.1 eligible

Sydney Harbour Paints use only premium grade raw materials. Our manufacturing processes are designed for maximum performance with

minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Excellent for use on garden furniture, exterior plywood, weatherboard, shingle or interior furniture and floorboards.

COLOR:

Translucent black.

LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

Not suitable for decking and not suitable for treated timber.

PREPARATION:

The substrate should be sanded to expose clean bare timber free from paint, grease, oil, mold and previous coatings. Timber should be dry and free

of contaminants. On previously painted surfaces *all* paint must be removed, and surface stripped bare and thoroughly sanded before application.

When using Palm Beach Black over exterior timbers that are oily in nature, such as brush box, blackbutt, jarrah, spotted gum, teak and other hardwoods that have a natural oiliness or waxiness, we recommend allowing the timber to weather for at least 3 months. This is to allow the surface grain to open and the surface oils to dry out. Palm Beach Black, being water based, requires an absorbent non-oily substrate.

Prior to application on all exterior timber, clean the surface with a high strength timber cleaner to remove contaminants or residual oils. Follow manufacturer's application instructions and dry times.

If in doubt as to whether to proceed, apply a water bead test. If water beads on the timber surface the substrate may require further weathering or cleaning. If moisture is absorbed into the surface, then proceed with product application.

APPLICATION:

Stir thoroughly prior to use.

Apply Palm Beach Black in the shade. Apply 1 coat by brush, roller or spray, following the grain and ensuring even coverage. No longer than 3 minutes after application, wipe off excess paint with a soft, absorbent cloth so that the crevices and grain of the timber hold the color. If required apply a second coat to deepen the color, using the same method. Touch dry 30 minutes (using this method). Allow 4 hours dry time before applying second coat. Allow to dry 24 hours.

Do not try to achieve greater opacity or depth of color by the addition of further coats, as a buildup

of product can cause cracking and flaking of the finish.

COVERAGE RATES:

Covers approximately 600 to 800 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates. Please note that on weathered or aged timber with an open grain or more absorbent surface, coverage may be decreased.

CLEAN UP:

Water.

COMPLEMENTARY PRODUCTS:

Sydney Harbour's Palm Beach Black can be sealed and protected with Sydney Harbour's Clearcote (coverage 600 sq. ft. per gallon). Allow Palm Beach Black to dry for 72 hours before applying Clearcote. Test before use as a slight color variation may occur.

PACKAGING:

Sydney Harbour's Palm Beach Black is available in Pint, Quart and Gallon sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing.
Avoid eye contact. Avoid prolonged skin contact.
Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use.

MANUFACTURER/DISTRIBUTOR DETAILS:

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: admin@shpcompany.com

Web: www.SHPCompany.com