

WATTI ONEPAY

Multi-charger payment station

The Watti OnePay revolutionizes the convenience of EV charging by allowing app-less and cashless transactions.

Capable of servicing up to six chargers simultaneously, this unattended payment system eliminates the hassle of mobile apps. Simply arrive, pay, and charge. Watti OnePay enhances usability and accessibility at public charging locations, offering a seamless experience for every driver.



Multi-Charger Support

Serves up to 6 EV chargers simultaneously, reducing required payment terminals.



Cost Efficient & Lower Subscription Fees

Lowers deployment cost & reduces subscription fees through fewer terminals, providing long-term savings.



Universal Power Compatibility

Compatible with various power sources, including PoE 24-28VDC and 120, 208, 240V AC.



Fast Installation

Easy to install, requiring less time and technical expertise.



Dual Connectivity

Offers both cellular and Ethernet connections for reliable, flexible communication.



Cold Climate Adaptation

Features optional -40°C capability for use in extreme winter conditions.



App-Free Convenience

Eliminates the need for additional apps, addressing driver concerns about the inconvenience of managing multiple apps for on-the-go charging.



Universal Mounting

Options for wall or pedestal mounting.

ACCEPTS ALL MAJOR FORMS OF PAYMENT



TECHNICAL SPECIFICATIONS

Model Name	Watti OnePay	Watti OnePay Extreme	Watti OnePay Pedestal
Model Number	EAWIPT-6BL	EAWIPT-6BLX	EAWIPT-PED
Safety	CE, FCC, RoHS, CSA, CSAus 62368: IEC, EN, UL/cUL		
Installation Type	Wall or Pedestal Mount		
Communication			
Network	3G/4G/Ethernet/NFC		
Display	6.1cm (2.4in), 320 x 240px Colour Touch LCD Display Multi-Language Support		
Support	Buzzer and Speaker for Customer Support		
Power			
Power Supply	12 ~ 42V DC, 85 ~ 305V AC		NA
Environmental			
Operating Temperature	-30°C to 85°C (-22°F to 185°F)	-40°C to 85°C (-40°F to 185°F)	-40°C to 85°C (-40°F to 185°F)
Storage Temperature	-20°C to 55°C (-4°F to 131°F)		-40°C to 85°C (-40°F to 185°F)
Humidity Rating	25% to 95% (non-condensing)		100%
Mechanical			
Product Weight	2.4kg (5.2lbs)	2.7kg (5.6lbs)	30.7kg (67.7lbs)
Product Dimensions (WxHxD)	16cm x 26cm x 9cm (6.3in x 10.24in x 3.56in)		20.3cm x 15.3cm x 10cm (8in x 6.025in x 4in)
Protections			
Dust & Water Resistance	IP55		
Flammability	UL-94 V0		
Security	DES, 3DES, AES, RSA, ECC, SHA1		
Environmental	Internal Shock/Tilt Detector, Over Voltage, Over Current, Short Circuit Protections		
Hardware			
Material	Aluminum		Aluminum