



KINGPINLESS SOLUTIONS

- Eliminates kingpin failure and made to handle shock and impact
- Ideal for power-towed applications and rugged applications
- Precision-machined raceway enhances ergonomics and safety

FACTORY BRAKE & TOE GUARD OPTIONS



110 CONTENDER SERIES CASTERS

Tread Width: 2"
Capacity: Up to 2,000 lbs.

Wheel Diameters: 4", 5", 6", 8"
Brake: Poly Lock (only available on 6" and 8"), Poly Cam, Face Contact
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



310 CONTENDER SERIES CASTERS

Tread Width: 3"
Capacity: Up to 4,100 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Poly Lock, Poly Cam, Face Contact
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



410 CONTENDER SERIES CASTERS

Tread Width: 3"
Capacity: Up to 5,400 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Poly Lock, Poly Cam, Face Contact
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



610 CONTENDER SERIES CASTERS

Tread Width: 3", 4"
Capacity: Up to 9,500 lbs.

Wheel Diameters: 6", 8", 10", 12", 14"
Brake: Poly Lock, Poly Cam, Face Contact
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard

SPRING-LOADED SOLUTIONS

- Protect valuable equipment and flooring
- Reduce unwanted vibration
- Reduce operating noise



141 SERIES CONTENDER KINGPINLESS POLY SPRING CASTERS

Tread Width: 2"
Capacity: Up to 1,500 lbs.

Wheel Diameters: 5", 6", 8"
Brake: Face Contact (only available on 6" and 8")
Accessories: Field-Installable Swivel Lock



S310 SERIES CONTENDER SPRING-LOADED KINGPINLESS CASTERS

Tread Width: 3"
Capacity: Up to 3,000 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Please Consult Factory
Accessories: Field-Installable Swivel Lock



S410 SERIES CONTENDER SPRING-LOADED KINGPINLESS CASTERS

Tread Width: 3"
Capacity: Up to 3,000 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Please Consult Factory
Accessories: Field-Installable Swivel Lock



S610 SERIES CONTENDER SPRING-LOADED KINGPINLESS CASTERS

Tread Width: 3"
Capacity: Up to 3,000 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Please Consult Factory
Accessories: Field-Installable Swivel Lock

3D CAD MODELS
AVAILABLE ONLINE

DUAL WHEEL SOLUTIONS

- Provides higher load ratings with lower overall heights
- Increases product stability for a safer footprint
- Can utilize softer wheels while maintaining higher load ratings



115 SERIES KINGPINLESS CASTERS

Tread Width: 2"
Capacity: Up to 2,000 lbs.

Wheel Diameters: 4", 5", 6", 8"
Brake: Please Consult Factory
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



315/415 SERIES KINGPINLESS CASTERS

Tread Width: 3"
Capacity: Up to 5,400 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Poly Lock
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



615 SERIES KINGPINLESS CASTERS

Tread Width: 3", 4", 5"
Capacity: Up to 12,000 lbs.

Wheel Diameters: 6", 8", 10", 12"
Brake: Poly Lock, Toe Guard
Accessories: Field-Installable Swivel Lock, Factory-Installed Toe Guard



850 SERIES KINGPINLESS CASTERS

Tread Width: 3", 4", 5", 6", 9"
Capacity: Up to 30,000 lbs.

Wheel Diameters: 6", 10", 12", 16", 18"
Brake: Face Contact
Accessories: Factory-Installed Swivel Lock



298 SERIES AVIATION GROUND EQUIPMENT CASTERS

Tread Width: 4-1/2", 6", 9"
Capacity: Up to 20,000 lbs.

Wheel Diameters: 12", 16-1/4", 18"
Brake: Face Contact
Accessories: Factory-Installed Swivel Lock



94/95 SERIES CASTERS

Tread Width: 4.8", 5.7", 6.5", 6.9", 7.5"
Capacity: Up to 3,630 lbs.

Wheel Diameters: 16", 18", 21", 23", 25"
Brake: Face Contact
Accessories: Factory-Installed Swivel Lock

MANY OTHER AEROSPACE AND GROUND SUPPORT SELECTIONS ARE AVAILABLE.


PLEASE VISIT OUR WEBSITE OR CONSULT OUR ENGINEERING TEAM FOR YOUR CASTER NEEDS.

AIR CARGO

ALBION

Wheel Diameter (Inches)
Tread Width (Inches)
Capacity (Lbs)
Overall Height (Inches)
Approx. Wt. (Lbs)
Caster Number

PRIORITY PREMIER™ RECTANGULAR PLATE YELLOW DICHROMATE FINISH



2-1/4 (58mm)	1-3/8 (34mm)	450	3-3/4 (96mm)	1-3/4	03XN02028S004C
-----------------	-----------------	-----	-----------------	-------	----------------

Double-sealed precision ball bearing

PRIORITY PREMIER™ RECTANGULAR PLATE YELLOW DICHROMATE METAL TOE GUARD



2-1/4 (58mm)	1-3/8 (34mm)	450	3-3/4 (96mm)	1-3/4	03XN02028S001C
-----------------	-----------------	-----	-----------------	-------	----------------

Double-sealed precision ball bearing

Faultless

Wheel Diameter (Inches)
Tread Width (Inches)
Capacity (Lbs)
Overall Height (Inches)
Swivel Radius (Inches)
Caster Number

POLYFLEX BROWN (NEEDLE BEARING) WITH A PLATE



2-3/4	1-3/8	375	4-1/32	2-3/8	27015
-------	-------	-----	--------	-------	-------

POLYFLEX GREY WITH TOE GUARD (NEEDLE BEARING) WITH A PLATE



2-3/4	1-3/8	375	4-1/32	2-3/16	27016
-------	-------	-----	--------	--------	-------

MANY OTHER AVIATION INDUSTRY, MANUFACTURING, AND ERGONOMIC SOLUTIONS ARE AVAILABLE.

PLEASE VISIT OUR WEBSITE OR CONSULT OUR ENGINEERING TEAM FOR YOUR CASTER NEEDS.



— A BRAND OF —
COLSON GROUP THE GLOBAL LEADER
IN CASTERS AND WHEELS

800 North Clark Street
Albion, MI 49224
Phone: 800-835-8911

ALBION