

# LUMUX

## BOLLARD

BL900

DATE: \_\_\_\_\_  
PROJECT: \_\_\_\_\_  
FIRM: \_\_\_\_\_  
CATALOG NO.: \_\_\_\_\_  
COMMENTS: \_\_\_\_\_

**COMING SOON!**



**BL900 from Lumux is an elegant, architectural bollard that excels at defining spaces, both during the day and at night.**

BL900 offers a distinctively contemporary, minimalistic design. Ideal for illuminating paths and plazas, BL900 is a powerful outdoor LED solution. BL900 is constructed from heavy-duty aluminum extrusion, providing durability that meets the highest standards. Part of the Lumux bollard lighting collection, this luminaire is offered in tall (BL900) and short (BL900S) models.

up to **3,000** lm    **30**W    up to **100** lm/W

Content of specification sheet subject to change

# LUMUX

## BOLLARD BL900

BL900 is an elegant medium-height gateway, path, and plaza light with a modern design.

### Ordering Guide

Catalog No.	LED Color	Color Temp <sup>1</sup>	Voltage	Finish	Options <sup>2</sup>
BL900	White	2700K	120-277v	Black	<input type="checkbox"/> 0-10v Dimming <input type="checkbox"/> GFCI Dual Recepticle <input type="checkbox"/> Occupancy Sensor <input type="checkbox"/> Photocell
		3000K		White	
		3500K		Silver	
		4000K		Bronze	
				Custom RAL <sup>2</sup>	

<sup>1</sup>Consult factory for additional options

<sup>2</sup>Consult factory for additional pricing

Catalog No.: \_\_\_\_\_

Performance Specifications	
Flux 3,000 lm	LER 100 lm/W
Power 30W	120-277v input voltage
Starting temp. rated to -20°F	GFCI dual recepticle option
Dimmable driver (0-10v) option	Occupancy sensor option
Lumen Maintenance*: TBD	Photocell option

Environmental Specifications	
BUG rating: B0-U0-G0	
CRI 80	Color temperature options
IP65	ETL listed for wet-locations
Effective Projected Area 2ft <sup>2</sup>	Marine Grade option
5-year limited warranty	Made in the USA

### Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
BL900	3,000 lm	3,000 lm	3,000 lm	3,000 lm	30W



**Housing:** Heavy-duty construction of corrosion resistant, low-copper extruded aluminum. All fasteners are vandal resistant stainless-steel.

**Lens:** Sealed one-piece, shatter-proof, UV-rated clear glass diffuser.

**Gasket:** Closed-cell silicone foam gasket that seals out moisture, dust, and insects, for weather tight operation.

**Mounting:** Secures with galvanized anchor bolts.

**Installation:** Please refer to installation instructions.

**Finish:** Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

### Dimensions

\*Lumen Maintenance Report: TBD

Content of specification sheet subject to change

# LUMUX

---

## LUMINAIRES IN THIS COLLECTION



**BL900**



**BL900S**