

TE:	DATE:
TT:	PROJECT:
M:	FIRM:
O.:	CATALOG NO.:
TS:	COMMENTS:

STEP LIGHT SL2000 SERIES

































SL2000R

SL2000 from Lumux is an elegant architectural step light, precision engineered for durability and performance.

SL2000 offers a distinctively minimalist ADA LED solution, ideal for illuminating steps, facades, and walls along access ways. SL2000Q offers a square faceplate whereas SL2000S is round. SL2000 step lights are energy-efficient for long-lasting indoor and outdoor applications. SL2000 features a powder coated faceplate retaining a recessed impact-resistant glass diffuser, seamlessly integrated to a durable diecast aluminum housing, with a flush glare-hood to shield the light source.

up to

65 lm

 3_{W}

up to **22** lm/W

Content of specification sheet subject to change



DATE:	
PROJECT:	
FIRM:	
CATALOG NO.:	
COMMENTS:	

STEP LIGHT

SL2000 SERIES

SL2000 is an elegant ADA step and wall light with a modern design and faceplate finish options, perfect for campus, resort and residential use.

Ordering Guide

Catalog No.	Wattage	LED Color	Color Temp ¹	Voltage	Finish	Options ²
SL2000Q	3W	White	2700K	120-277v	Black	□ 0-10V Dimming
SL2000R		Amber-TF	3000K		White	
			3500K		Silver	
			4000K		Bronze	
					Custom RAL ²	

¹Consult factory for additional options

²Consult factory for additional pricing

Performance Specifications			
Flux 65 lm (4000K)	LER 22 lm/W		
Power 3W	120-277v input voltage		
Starting temp. rated to -20°F			
0-10v Dimming Driver option			
Lumen Maintenance*: tbd			

3" 34" 34" 33" SL2000Q SL2000R

Dimensions

Catalog No.: _

Environmental Specifications		
BUG rating: tbd	Amber-TF turtle-friendly option	
CRI 80	Color temperature options	
IP65	ETL listed for wet-locations	
Effective Projected Area: n/a	Marine Grade option	
5-year limited warranty	Made in the USA	

Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
SL2000Q	50 lm	55 lm	60 lm	65 lm	3W
SL2000R	50 lm	55 lm	60 lm	65 lm	3W

*Estimated lumens. For higher lumen packages, please consult the Lumux sales team.

Housing: SL2000 features a powder coated faceplate that is optionally square (SL2000Q) or round (SL2000R) mounted to a diecast low-copper aluminum housing with vandal-resistant stainless steel screws.

Lens: Sealed one-piece shatter-proof frosted glass diffuser.

Gasket: Closed-cell silicone foam gasket that seals out moisture, dust, and insects, for weather tight operation.

Mounting: Recessed mounted, with optional CPX concrete pour box provided.

Installation: Please refer to installation instructions.

Finish: Zinc-polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.


Light Engine: Standard constant current non-dimming driver powering high quality LEDs. 0-10v dimming driver optional.

Content of specification sheet subject to change

LUMUX

STEP LIGHT

SL SERIES COLLECTION



SL100H window



SL410SS



SL400SS



SL100H grill



SL2000Q



SL420SS



SL100



SL2000R



SL450SS