

LUMUX

STEP LIGHT SL550SS

DATE: _____
PROJECT: _____
FIRM: _____
CATALOG NO.: _____
COMMENTS: _____



The SL500SS Series are elegant architectural step lights, precision engineered in stainless steel for durability and performance.

The SL500SS Series luminaires offer a distinctively contemporary, minimalist design. Ideal for illuminating steps, facades, and walls along access ways, SL550SS step lights are powerful ADA LED solutions, energy-efficient for long-lasting indoor and outdoor applications. SL500SS Series luminaires feature a durable stainless steel faceplate mounted to a diecast aluminum housing retaining an impact-resistant glass diffuser with grill options.

up to
450 lm

12w

up to
38 lm/W

LUMUX

STEP LIGHT SL550SS

SL550SS is an elegant stainless steel ADA step and wall light with a modern design and turtle-friendly option, perfect for campus, resort and residential use.

Ordering Guide

Catalog No.	Wattage	LED Color	Color Temp ¹	Voltage	Finish	Options ²
SL550SS	12W	White Amber-TF	2700K 3000K 3500K 4000K	120-277v	Stainless Steel Black White Silver Bronze Custom RAL ²	<input type="checkbox"/> 0-10V Dimming

¹Consult factory for additional options

²Consult factory for additional pricing

Catalog No.: _____

Performance Specifications	
Flux 450 lm (4000K)	LER 38 lm/W
Power 12W	120-277v input voltage
Starting temp. rated to -20°F	
0-10v Dimming Driver option	
Lumen Maintenance*: tbd	

Environmental Specifications	
BUG rating: tbd	Amber-TF turtle-friendly option
CRI 80	Color temperature options
IP65	ETL listed for wet-locations
Effective Projected Area: n/a	Marine Grade option
5-year limited warranty	Made in the USA

Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
SL550SS	300 lm	325 lm	400 lm	450 lm	12W

For higher lumen packages, please consult the Lumux sales team.

Housing: SL500SS luminaires feature a stainless steel faceplate mounted to a diecast low-copper aluminum housing with vandal-resistant stainless steel screws.

Lens: Sealed one-piece shatter-proof frosted glass diffuser.

Gasket: Closed-cell silicone foam gasket that seals out moisture, dust, and insects, for weather tight operation.

Mounting: Recessed mounted, with optional CPX concrete pour box provided.

Installation: Please refer to installation instructions.

Finish: Stainless steel faceplate with optional zinc-polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Light Engine: Standard constant current non-dimming driver powering high quality LEDs. 0-10v dimming driver optional.



Dimensions

Content of specification sheet subject to change

LUMUX

STEP LIGHT SERIES COLLECTION



SL500SS



SLS100



SL400SS



SL532SS



SLR300RR



SL2024-9



SL550SS



SLS150



SL450SS



SL562SS



SL563SS



SL420SS