

LUMUX

STEP LIGHT SLS100 SERIES

DATE: _____
PROJECT: _____
FIRM: _____
CATALOG NO.: _____
COMMENTS: _____



SLS100



SLS130



SLS150

The SLS100 Series luminaires from Lumux are classic architectural step lights, precision engineered for durability and performance.

The SLS100 Series offers ADA LED solutions with a distinctively classic design, ideal for illuminating steps, facades, and walls along access ways. SLS Series step lights are energy-efficient for long-lasting indoor and outdoor applications. SLS Series luminaires feature a powder coated faceplate retaining an impact-resistant diffuser, seamlessly integrated to a durable diecast aluminum housing, with certain models featuring a protective grill or glare-hood to shield the light source.

up to
100 lm

3w

up to
37 lm/W

LUMUX

STEP LIGHT SLS100 SERIES

The SLS100 Series are classic architectural ADA step and wall lights with faceplate finish options, perfect for campus, resort & residential use.

Ordering Guide

Catalog No.	Wattage	LED Color	Color Temp ¹	Voltage	Finish	Options ²
SLS100	3W	White	2700K	120-277v	Black	<input type="checkbox"/> 0-10V Dimming
SLS130		Amber-TF	3000K		White	
SLS150		Red	3500K		Silver	
		Green	4000K		Bronze	
		Blue			Custom RAL ²	

¹Consult factory for additional options

²Consult factory for additional pricing

Catalog No.: _____

Performance Specifications	
Flux 100 lm (4000K)	LER 37 lm/W
Power 3W	120-277v input voltage
Starting temp. rated to -20°F	
0-10v Dimming Driver option	
Lumen Maintenance*: tbd	

Environmental Specifications	
BUG rating: tbd	Amber-TF turtle-friendly option
CRI 80	Color temperature options
IP65	ETL listed for wet-locations
Effective Projected Area: n/a	Marine Grade option
5-year limited warranty	Made in the USA

Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
SLS100	70 lm	80 lm	90 lm	100 lm	3W
SLS130	60 lm	70 lm	80 lm	90 lm	3W
SLS150	35 lm	40 lm	45 lm	50 lm	3W

*Estimated lumens. For higher lumen packages, please consult the Lumux sales team.

Housing: The SLS100 Series feature a powder coated faceplate enclosing diffuser mounted to a diecast low-copper aluminum housing with vandal-resistant stainless steel screws.

Lens: Sealed one-piece shatter-proof frosted glass diffuser.

Gasket: Closed-cell silicone foam gasket that seals out moisture, dust, and insects, for weather tight operation.

Mounting: Surface-mounted with mounting bracket to standard 3" and 4" junction box.

Installation: Please refer to installation instructions.

Finish: Zinc-polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Light Engine: Standard constant current non-dimming driver powering high quality LEDs. 0-10v dimming driver optional.



SLS100



SLS130



SLS150

Dimensions

Content of specification sheet subject to change

LUMUX

STEP LIGHT


SLS SERIES COLLECTION



SLS100



SLS250



SLS1000



SLS130



SLS650



SLS1400



SLS150



SLS750



SLS1500



SLS350



SLS755

Content of specification sheet subject to change