

LUMUX

STEP LIGHT

SLS250

DATE: _____
PROJECT: _____
FIRM: _____
CATALOG NO.: _____
COMMENTS: _____



SLS250 from Lumux is a classic architectural step light, precision engineered for durability and performance.

SLS250 offers an ADA LED solution with a distinctively classic design, ideal for illuminating steps, facades, and walls along access ways. SLS Series step lights are energy-efficient for long-lasting indoor and outdoor applications. SLS Series luminaires feature a powder coated faceplate retaining an impact-resistant diffuser, seamlessly integrated to a durable diecast aluminum housing, with certain models featuring a protective grill or glare-hood to shield the light source.

up to
130 lm

5w

up to
26 lm/W

LUMUX

STEP LIGHT SLS250

SLS250 is a classic architectural ADA step and wall light with faceplate finish options, perfect for campus, resort and residential use.

Ordering Guide

Catalog No.	Wattage	LED Color	Color Temp ¹	Voltage	Finish	Options ²
SLS250	5W	White Amber-TF	2700K 3000K 3500K 4000K	120-277v	Black White Silver Bronze Custom RAL ²	<input type="checkbox"/> 0-10V Dimming

¹Consult factory for additional options

²Consult factory for additional pricing

Catalog No.: _____

Performance Specifications	
Flux 130 lm (4000K)	LER 26 lm/W
Power 5W	120-277v input voltage
Starting temp. rated to -20°F	
0-10v Dimming Driver option	
Lumen Maintenance*: tbd	

Environmental Specifications	
BUG rating: tbd	Amber-TF turtle-friendly option
CRI 80	Color temperature options
IP65	ETL listed for wet-locations
Effective Projected Area: < 0.5 sq.ft.	Marine Grade option
5-year limited warranty	Made in the USA

Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
SLS250	110 lm	120 lm	125 lm	130 lm	5W

For higher lumen packages, please consult the Lumux sales team.

Housing: SLS250 features a powder coated faceplate enclosing diffuser mounted to a diecast low-copper aluminum housing with vandal-resistant stainless steel screws.

Lens: Sealed one-piece shatter-proof frosted polycarbonate diffuser.

Gasket: Closed-cell silicone foam gasket that seals out moisture, dust, and insects, for weather tight operation.

Mounting: Surface-mounted with mounting bracket to standard 3" and 4" junction box.

Installation: Please refer to installation instructions.

Finish: Zinc-polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Light Engine: Standard constant current non-dimming driver powering high quality LEDs. 0-10v dimming driver optional.



Dimensions

Content of specification sheet subject to change

LUMUX

STEP LIGHT


SLS SERIES COLLECTION



SLS100



SLS250



SLS1000



SLS130



SLS650



SLS1400



SLS150



SLS750



SLS1500



SLS350



SLS755

Content of specification sheet subject to change