

LUMUX

UP / DOWN LIGHT

UD110 & UD410

DATE: _____
PROJECT: _____
FIRM: _____
CATALOG NO.: _____
COMMENTS: _____



UD Series luminaires from Lumux are elegant architectural up and down lights, precision engineered for durability and performance.

The UD Series offers a distinctive contemporary design. Ideal for illuminating walkways, porches and porticos, or as accent lighting, Lumux UD luminaires are powerful outdoor LED solutions. The UD Series features diecast aluminum housings with a shielded light source to enhance visual comfort, and UD410 features an optional integral battery pack delivering 1,000 lm over 90 min. UD Series luminaires are energy-efficient for long-lasting indoor and outdoor applications.



2,000 lm **18** w up to **110** lm/W

LUMUX

UP / DOWN LIGHT

UD110 & UD410

The UD Series are high-efficacy wall mount luminaires with uplight and downlight options. UD410 features an optional integral battery pack.

Ordering Guide

Catalog No.	Beam Angle	Wattage	LED Color	Color Temp ¹	Voltage	Finish	Options ²
UD110	20°	19W	White	2700K	120-277v	Black	<input type="checkbox"/> Uplight & Downlight <input type="checkbox"/> Uplight only <input type="checkbox"/> Downlight only <input type="checkbox"/> 0-10v Dimming <input type="checkbox"/> Integral Battery Pack
UD410			Amber-TF	3000K		White	
			Red	3500K		Silver	
			Green	4000K		Bronze	
			Blue			Custom RAL ²	

¹Consult factory for additional options

²Consult factory for additional pricing

Catalog No.: _____

Performance Specifications	
Flux 2,000 lm (4000K)	LER 110 lm/W (4000K)
Power 19W	120-277v input voltage
Starting temp. rated to -20°F	Integral Battery Pack option
0-10v Dimming Driver option	
Lumen Maintenance*: L70 > 60K hrs	

Environmental Specifications	
Downlight BUG Rating B1-U0-G0	Amber-TF turtle-friendly option
CRI 80	Color temperature options
IP65	ETL listed for wet-locations
Effective Projected Area: 1 sq. ft.	Marine Grade option
5-year limited warranty	Made in the USA

Delivered Lumens & Wattage per color temperature:

	2700K	3000K	3500K	4000K	WATTS
UD410/110	1350 lm	1500 lm	1800 lm	2000 lm	19W
UD410-IBP	1000 lm	1000 lm	1000 lm	1000 lm	10W

For higher lumen packages, please consult the Lumux sales team.

Housing: Heavy-duty construction of corrosion resistant, low copper diecast aluminum, enclosing a glass optic and anodized aluminum reflector with a step baffle frame, secured with vandal resistant, stainless-steel screws.

Lens: Sealed one-piece shatter-proof clear glass optic.

Gasket: Closed-cell silicone foam gasket seals out moisture, dust, and insects, for weather-tight operation. IP65 - ETL listed for wet-locations.

Mounting: Surface mounted to wall or column. Mounting bracket provided fits any standard 3" or 4" junction box.

Installation: Please refer to installation instructions.

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Light Engine: Constant Current driver with optional 0-10v dimming, powering high quality LEDs.

Integral Battery Pack: Optional emergency 10W IBP for UD410 provides 1,000 lumens with 90 minute battery life.



*Lumen Maintenance Report: Nichia
Test Documentation No.: NFSW757GT-V3

Content of specification sheet subject to change


LUMUX

UP & DOWN LIGHTS

LUMINAIRES IN THE COLLECTION



DL100



DL500



UD110



UD410



UD420



UD430



UD440

LUMUX LIGHTING

7803 Industry Ave, Pico Rivera, CA 90660
sales@lumux.com | 562-801-5100

Content of specification sheet subject to change