LUMUX WALL SCONCES WS884

The Lumux Wall Sconce ("WS") series combines architectural design and quality with high performance, and features a range of vandal resistant, wall and ceiling mounted luminaries with a variety of grill and visor options. Designed for accent lighting of walls and facades, the Lumux WS series is constructed from the highest quality components and is built for optimal performance in any environment while

offering elegant and attractive form factors.

DATE:	
PROJECT:	
FIRM:	
ATALOG NO.:	
COMMENTS:	













Housing: Heavy-duty construction of one-piece, corrosion resistant, low-copper (<1% copper) die-cast aluminum. Enclosed lens secured with vandal resistant, stainless-steel screws.

Lens: One piece injection molded white opal, 1/8" thick, shatter proof polycarbonate lens.

Mounting: Surface mounted, wall or ceiling

Installation: Mounting bracket provided that fits any standard 3.0" or 4.0" J-Box

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Driver: Constant current and universal input voltage 120/277V, starting temperature rated at -20°F. Dimmable option available (0-10v).

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations


Wattage: 24W

Color Temperature: 2700K / 3000K / 3500K / 4000K

Delivered Lumens: 2700K 3000K 3500K 4000K 1134Lm 1260Lm 1400Lm 1554Lm Please consult factory for higher lumen packages CRI: 90

Warranty: 5 year limited warranty

Dimensions:



LUMUX WALL SCONCES WS884

DATE:

PROJECT: FIRM:

CATALOG NO.:

COMMENTS:

Ordering Guide:

Catalog No.	LED Color	Color Temp ¹	Voltage	Finish	Options ²
WS884	White	2700K	120/277	Black	Dimmable driver (0-10v)
	Amber	3000K		White	
		3500K		Silver	
		4000K		Bronze	
				Custom RAL ²	

¹Consult factory for additional options

²Consult factory for additional options

Catalog No.: