

## MATERIAL SAFETY DATA SHEET

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: LANG DENTAL MFG. CO., INC.  
175 MESSNER DRIVE  
WHEELING, IL 60090  
U.S.A.

TELEPHONE: PRODUCT INFORMATION: (800) 222-5264 or (847) 215-6622

EMERGENCY CONTACT: INFOTRAC 24 HOURS CHEMICAL RESPONSE SYSTEM  
(800) 535-5053 or (352) 323-3500

PRODUCT: FLEXACRYL POWDER

PRODUCT NUMBERS: 0920, 0930, 0950, 0970, 0980, 0923, 0934, 0956, 1123, 1134, 1156

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S):	CAS NUMBER:	% :
Polymer	9003-42-3	< 99
Benzoyl Peroxide	94-36-0	< 2

### 3. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Skin or Eyes, Inhalation of dusts.  
Avoid inhalation of dust. Keep dust out of eyes to prevent possible irritation.

EFFECTS OF OVER EXPOSURE: OSHA classifies this material as Particulates, Not Otherwise Classified. Eyes, skin and respiratory tract may be irritated by gross overexposure to Particulates, Not Otherwise Classified, no matter how they are generated. Not expected to cause any harmful effects if ingested. Ingestion of large amounts may be irritating if product is swallowed, may cause nausea, headache, vomiting and/or diarrhea.

CARCINOGENICITY: IARC lists Benzoyl Peroxide as unclassifiable as to carcinogenicity to humans. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH as carcinogens.

### 4. FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Get medical help if discomfort persists.  
EYES: Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.  
SKIN: Wash with soap and water. Get medical help if discomfort persists.  
INGESTION: Do not induce vomiting. Drink plenty of water or milk IMMEDIATELY. If vomiting, continue to offer water Or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.  
CLOTHING: Remove contaminated clothing, wash thoroughly before reuse.

### 5. FIRE FIGHTING MEASURES

FLASH POINT: 304 °C (580 °F) FLAMMABLE LIMIT, AIR VOL % LOWER: NA AUTOIGNITION TEMPERATURE: NE  
UPPER: NA

EXTINGUISHER METHOD: Water, carbon dioxide, dry chemical  
SPECIAL FIRE FIGHTING PROCEDURES: Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust in air producing a fire hazard and possible explosion hazard if exposed to ignition source.

FIRE AND EXPLOSION HAZARDS: For bulk size. Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust.

EXPLOSION HAZARD: Firefighters should wear self-contained breathing apparatus.

SENSITIVE TO MECHANICAL IMPACT: For Polymer: No

SENSITIVE TO STATIC DISCHARGE: For Polymer: No

## MATERIAL SAFETY DATA SHEET

### 6. ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Before cleaning any spill or leak, individuals involved must wear appropriate Personal Protective Equipment (eg. goggles, gloves). Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up spills. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

### 7. HANDLING AND STORAGE

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and housekeeping. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Keep only in original container. Keep container closed to prevent water absorption and contamination.

**INDUSTRIAL HYGIENE PRACTICES:** Avoid prolonged contact with the product. Use in a well-ventilated location (eg. local exhaust ventilations, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

**STORAGE TEMPERATURE:** Preferably not exceeding 35 °C.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**VENTILATION:** When working with large quantities of product provide adequate ventilation (eg. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

**RESPIRATORY PROTECTION:** No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR SS 1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, it's provinces, EC member states, or Australia.

**VENTILATION:** Local exhaust at processing equipment.

**EYE PROTECTION:** Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to U.S. OSHA 29CFR SS1910.133. Canadian standards, or the European Standard EN 166. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

**PROTECTIVE GLOVES:** If anticipated that prolonged & repeated skin contact will occur during use of this product, wear gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR SS 1910.138, the appropriate standards of Canada, of the EC member states.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** NA

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** ND

**VAPOR PRESSURE:** NA

**PERCENT VOLATILE WW%:** NA

**VAPOR DENSITY (AIR=1):** NA

**EVAPORATION RATE:** NA

**SOLUBILITY IN WATER:** Insoluble

**APPEARANCE AND ODOR:** Fine clear to pigmented powder.  
Faint odor in bulk.

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Heating above 240 °C (464 °F)

**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Methacrylate monomer and oxides of carbon when burned.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## MATERIAL SAFETY DATA SHEET

### 11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: This product has NOT been tested on animals to obtain toxicology data. There is toxicology data for the components of the product, which is found in scientific literature. This data has not been presented in this document.

MUTAGENICITY DATA: For Polymer – None listed.

REPRODUCTIVE TOXICITY DATA: For Polymer – None listed.

### 12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY: There is no specific data available for this product, however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

ENVIRONMENTAL FATE: There is no specific data available for this product.

### 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose of properly in accordance with federal, state and local regulations.

DISPOSAL OF EMPTY CONTAINERS: For bulk only. Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

### 14. TRANSPORTATION INFORMATION

DOT/UN SHIPPING NAME: Polymer, NOI  
Non-hazardous

### 15. REGULATORY INFORMATION

Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin.

Safety Phrases: S3 Keep in a cool place.  
S7 Keep container tightly closed.  
S9 Keep container in a well-ventilated place.  
S20 When using do not eat or drink.  
S29 Do not empty into drains.  
S37/39 Wear suitable gloves and eye/face protection.

#### CANADIAN REGULATIONS:

WHMIS: This product has been classified in accordance with the hazardous criteria of the CPR and the MSDS contains all the information required by the CPR. All of the components of this material are listed on the Canadian DSL.

TSCA: For use in FDA regulated products only

### 16. OTHER INFORMATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:  
HEALTH = 1  
FLAMMABILITY = 1  
REACTIVITY = 0

The data sheet was prepared in accordance with Directive 91/155/EEC

The above information has been gathered from reliable sources and is believed to be correct. However, the information is provided without any warranty, either expressed or implied. Lang Dental Mfg. Co., Inc. shall not be held liable for any damage resulting from the handling of or contact with the above product.

=====

UPDATE: 01/15/09