Page: 1



# Material Safety Data Sheet

RHODORSIL V-1065 PART A

Date Prepared: 11/02/09 Supersedes Date: 10/17/06

# 1. PRODUCT AND COMPANY DESCRIPTION

Bluestar Silicones 911 E. White Street Rock Hill, SC US

Emergency Phone Numbers:

FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT CONTACT: CHEMTREC (800-424-9300 within the United States or 703-527-3887 for international collect calls).

For Product Information: 803-329-5260

Chemical Name or Synonym: SILICONE

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

		OSHA	
Component	CAS Reg Number	Hazard	Percentage
POLYDIMETHYLSILOXANE, HYDROXY TERMINATED	70131-67-8	N	40 - 70
SILICA, AMORPHOUS, TREATED	68909-20-6	N	10 - 30
POLY(DIMETHYL)SILOXANE	63148-62-9	N	10 - 30
TITANIUM DIOXIDE	13463-67-7	Υ	0.1 - 1

# 3. HAZARDS IDENTIFICATION

#### A. EMERGENCY OVERVIEW:

Physical Appearance and Odor: white viscous liquid, odorless.

Warning Statements:

CAUTION! MAY CAUSE SKIN AND EYE IRRITATION.

B. POTENTIAL HEALTH EFFECTS:

Acute Eye:

2

May cause irritation.

#### Acute Skin:

Low acute dermal toxicity. May cause irritation.

#### Acute Inhalation:

Inhalation not likely.

#### Acute Ingestion:

Low acute oral toxicity.

#### Chronic Effects:

This product contains ingredients that are considered to be probable or suspected human carcinogens (see Section 11 - Chronic).

# FIRST AID MEASURES

#### FIRST AID MEASURES FOR ACCIDENTAL:

# Eye Exposure:

In case of contact, immediately absorb excess with clean absorbent cloth or cotton. Then, hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention if irritation develops or persists or if visual changes occur.

#### Skin Exposure:

Immediately wipe excess material off skin with a dry cloth; then wash skin with plenty of soap and water. Seek medical attention if irritation develops or persists.

#### Inhalation:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

#### Ingestion:

NEVER attempt to induce vomiting. Consult a doctor if necessary. Rinse mouth out with water.

#### MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

No specific information found.

# NOTES TO PHYSICIAN:

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Treat symptomatically. No specific antidote available.

#### BIRD BIGHTING MEASURES

#### FIRE HAZARD DATA:

## Flash Point:

Not Applicable

#### Extinguishing Media:

Recommended: dry chemical, foam, carbon dioxide.

## Special Fire Fighting Procedures:

Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Cool containers exposed to fire with water.

## Unusual Fire and Explosion Hazards:

Product will burn under fire conditions.

# Hazardous Decomposition Materials (Under Fire Conditions):

formaldehyde oxides of carbon silica

# 6. ACCIDENTAL RELEASE MEASURES

# Evacuation Procedures and Safety:

Wear appropriate protective gear for the situation. See Personal Protection information in Section 8. CAUTION: Spilled material may make the floor slippery. Do not leave traces of product on floors, ladders, etc., as this may present a slipping hazard.

## Containment of Spill:

Follow procedure described below under Cleanup and Disposal of Spill.

#### Cleanup and Disposal of Spill:

Absorb with an inert absorbent. Scrape up and place in appropriate closed container (see Section 7: Handling and Storage). Clean up residual material with an appropriate solvent like paint thinner or mineral spirits, provided that there is good ventilation and no sources of ignition.

# Environmental and Regulatory Reporting:

Do not flush to drain.

# 7. HANDLING AND STORAGE

# Minimum/Maximum Storage Temperatures:

< 32 C (90 F)

#### Handling:

Avoid breathing vapors and mists. Avoid direct or prolonged contact with

skin and eyes. DO NOT ALLOW TO FREEZE.

#### Storage:

Store in tightly closed containers. Store in an area that is clean, dry, well-ventilated.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Introductory Remarks:

These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and piping systems for maintenance and repairs. Waste resulting from these procedures should be handled in accordance with Section 13: Disposal Considerations.

Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers.

This product can form formaldehyde vapors when heated to temperatures above 150 degrees C in the presence of air. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin, and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

# Exposure Guidelines:

Exposure limits represent regulated or recommended worker breathing zone concentrations measured by validated sampling and analytical methods, meeting the regulatory requirements. The following limits apply to this material, where, if indicated, S=skin and C=ceiling limit:

# TITANIUM DIOXIDE

Notes TWA STEL ACGIH 10 mg/cu m 0SHA 10 mg/cu m

# Engineering Controls:

Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure control techniques may be used to effectively minimize employee exposures: general area dilution/exhaust ventilation.

# Respiratory Protection:

When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

Under normal conditions, in the absence of other airborne contaminants, the following devices should provide protection from this material up to the conditions specified by the appropriate OSHA, WHMIS or ANSI standard(s): Air-purifying (half-mask/full-face) respirator with cartridges/canister approved for use against organic vapors.

# Eye/Face Protection:

Eye and face protection requirements will vary dependent upon work environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material.

It is generally regarded as good practice to wear a minimum of safety glasses with side shields when working in industrial environments.

#### Skin Protection:

Skin contact should be minimized through use of gloves and suitable long-sleeved clothing (i.e., shirts and pants). Consideration must be given both to durability as well as permeation resistance.

#### Work Practice Controls:

Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this material:

- (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
- (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
- (3) Wash exposed skin promptly to remove accidental splashes or contact with this material.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical properties here represent typical properties of this product. Contact the business area using the Product Information phone number in Section 1 for its exact specifications.

# Physical Appearance:

white viscous liquid.

## Odor:

odorless.

#### pH:

Not Applicable

# Specific Gravity:

1.12 at 23 C (73 F).

Water Solubility:

insoluble

Melting Point Range:

Not Available

Boiling Point Range:

Not Available

Vapor Pressure:

< 0 mmHg at 0 C (32 F)

Vapor Density:

Not Available

# 10. STABILITY AND REACTIVITY

# Chemical Stability:

This material is stable under normal handling and storage conditions described in Section 7.

#### Conditions To Be Avoided:

combustible materials heat open flame spark

#### Materials/Chemicals To Be Avoided:

strong bases strong acids strong oxidizing agents

The Following Hazardous Decomposition Products Might Be Expected:

Decomposition Type: thermal dimethylcyclosiloxanes methylphenylcyclosiloxanes

Decomposition Type: oxidative/thermal

formaldehyde

Hazardous Polymerization Will Not Occur.

Avoid The Following To Inhibit Hazardous Polymerization: not applicable

# 11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation:

No test data found for product.

Acute Skin Irritation:

No test data found for product.

Acute Dermal Toxicity:

No test data found for product.

Acute Respiratory Irritation:

No test data found for product.

Acute Inhalation Toxicity:

No test data found for product.

Acute Oral Toxicity:

No test data found for product.

Chronic Toxicity:

This product contains the substances that are considered to be "probable" or "suspected" human carcinogens as follows:

Ingredient Name
TITANIUM DIOXIDE

Regulatory Agency Listing Carcinogen
OSHA IARC NTP ACGIH
No 2B No No

# 12. ECOLOGICAL INFORMATION

Ecotoxicological Information:

No data found for product.

Chemical Fate Information:

No data found for product.

# 13. DISPOSAL CONSIDERATIONS

# Waste Disposal Method:

Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Please be advised that state and local requirements for waste disposal may be more restrictive or otherwise different from federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material.

# Container Handling and Disposal:

Any containers or equipment used should be decontaminated immediately after use.

EPA Hazardous Waste - NO

#### 14. TRANSPORTATION INFORMATION

Transportation Status: IMPORTANT! Statements below provide additional

data on listed DOT classification.

The listed Transportation Classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

US Department of Transportation

Shipping Name:

NOT REGULATED

# 15. REGULATORY INFORMATION

#### **Inventory Status**

Inventory	Status
UNITED STATES (TSCA)	Υ
CANADA (DSL)	Υ
EUROPE (EINECS/ELINCS)	Р
AUSTRALIA (AICS)	Υ
JAPAN (MITI)	Υ
SOUTH KOREA (KECL)	Υ

Y = All ingredients are on the inventory.

E = All ingredients are on the inventory or exempt from listing.

 $\mathsf{P}=\mathsf{One}$  or more ingredients fall under the polymer exemption or are on the no longer polymer list. All other ingredients are on the inventory or exempt from listing.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing.

#### FEDERAL REGULATIONS

# Inventory Issues:

All functional components of this product are listed on the TSCA Inventory.

## SARA Title III Hazard Classes:

Fire Hazard - NO
Reactive Hazard - NO
Release of Pressure - NO
Acute Health Hazard - YES
Chronic Health Hazard - YES

# STATE REGULATIONS:

This product does not contain any components that are regulated under California Proposition 65.

#### 16. OTHER INFORMATION

# National Fire Protection Association Hazard Ratings -- NFPA(R):

- l Health Hazard Rating--Slight
- 1 Flammability Rating--Slight
- O Instability Rating--Minimal

# National Paint & Coating Hazardous Materials Identification System--HMIS(R):

- 1 Health Hazard Rating--Slight
- 1 Flammability Rating--Slight
- O Reactivity Rating--Minimal

#### Reason for Revisions:

Change and/or addition made to Section 4.

# Key Legend Information:

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

TLV - Threshold Limit Value

PEL - Permissable Exposure Limit

TWA - Time Weighted Average

STEL - Short Term Exposure Limit

NTP - National Toxicology Program

IARC - International Agency for Research on Cancer

ND - Not determined

Bluestar - Bluestar Silicones Established Exposure Limits

#### Disclaimer:

The information herein is given in good faith but no warranty, expressed or implied, is made.

# \*\*End Of MSDS Document\*\*