NR CAYMAN GT3 REAR BUMPER with FINNED DIFFUSER

For 987.1 and 987.2 Cayman





- Remove rear bumper. All original mounting hardware is resued on new GT3 bumper
- If you want to use your bumper guards, you will need to cut openings in GT3 bumper like your original Cayman bumper (as shown in picture).
 This will allow GT3 bumper to slide over bumper guard supports. If you do not want to use your bumper guards on your GT3 bumper, remove the guard supports from the reinforcement.
- Slide GT3 bumper on the car using original hardware. Make any necessary adjustments to plastic mounting plates.
- Install mesh grill screen in air intakes after painting.
- We recommend painting finned diffuser matte black as shown in picture
- Remove bumper, prep and paint.

PREPPING INSTRUCTIONS FOR

FRP PARTS

Some of our NR Automobile body parts may come with a glossy gelcoat finish that has a wax smooth coating so the parts can be easily removed from the molds. These parts cannot be primered or painted without removing this wax coating. Use acetone or similar product to remove the wax coating.

Parts should be sanded with 150 grid paper. Use a sealer primer like PCL Poly Primer. This primer will fill in any small pin holes that may be present. Do not bake parts during the painting process.





BEFORE

Remove Mounting Plate



AFTER

- Enlarge the holes in the plastic mounting plate
- Adjust the plastic mounting plate so the opening is larger to allow the new bumper to fit in the channel between the mounting plate and the bottom of the fender.