






















# PARADOR

Laminate Urban Click 'In

Product quality		Tolerances (EN 13329)		
Formats	Length	1285 ± 0,50mm	<b>Squareness of the elements</b>	≤ 0,20mm
	Width	192 ± 0,10mm (bmax - bmin ≤ 0,20 mm)	<b>Determination of Linearity</b>	≤ 0,30 mm/m
	Thickness	8 ± 0,50mm (dmax - dmin ≤ 0,50 mm)	<b>Block alignment</b>	± 2 mm
<b>Packaging</b>	Pack: 9 elements / 2.22 m <sup>2</sup> / 15 kg Pallet: 52 packs / 115.44 m <sup>2</sup> / 780 kg		<b>Surface flushness</b>	average ≤ 0.10 mm max. ≤ 0.15 mm
<b>Guarantee (according Parador guarantee conditions)</b>			<b>Opening between installed elements</b>	average ≤ 0.15 mm max. ≤ 0.20 mm
Domestic area	15 years		<b>Flatness of elements</b>	fw, concave ≤ 0,15 % / fw, convex ≤ 0,20 % fl, concave ≤ 0,50 % / fl, convex ≤ 1,00 %
<b>Notes</b>	- not suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved			

Classification		
	Test method	Rating
 <b>Utility class 23</b> Domestic areas with intensive use	EN 13329	Living room, hall, kitchen, home office
 <b>Utility class 32</b> Commercial areas with medium use	EN 13329	Classrooms, small offices, shops
 Abrasion	EN 13329, Annex E	AC 4 (≥ 4.000 rev.)
 Impact resistance (small ball)	EN 17368	≥ 35mm
	EN 13329, Annex H	≥ 750mm
 Reaction to fire	EN 13501-1	C <sub>f</sub> s1
 Slip resistance	EN 13893	DS
 Staining resistance	EN 438-2	Category 1+2: level 5 Category 3: level 4
 Blue wool scale: Stage ≥ 6	EN ISO 4892-2	level 4
 Resistance to roller castor chairs	EN 425	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	0,073 m <sup>2</sup> *K/W ± 15%
 Moving a furniture leg	EN 424	Type 0, no visible changes
 Indentation-residual	ISO 24343-1	≤ 0,05mm
 Formaldehyde emission (E1 = 0.1 ppm)	EN 16516	E1
	ASTM D 6007 ASTM E 1333	CARB Phase 2 / EPA TSCA Title VI compliant
 Locking strength of mechanically assembled panels	ISO 24334	> 1 kN/m (long side) > 2 kN/m (short side)
 Acoustical - Impact noise reduction	ISO 717-2	14 dB (on Akustik-Protect 100)
 Dimensional stability	EN 13329, Annex C	≤ 0,9mm
 Thickness swelling	ISO 24336 (≤ 18 %)	≤ 12 %
Surface soundness	EN 13329, Annex D	≥ 1,25 N/mm <sup>2</sup>
Disposal		EAK-Code-number 20 01 38

Changed:	QM Parador	File:	20220401_PA_TDS_Laminat_Urban-Click-In_EN
Date:	01.04.2022	Latest update at:	www.parador.de/en/services/downloads/laminate-flooring
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.04.2022